

Tyrone Camarero Specifications



Camarero SS4C0TR-12L

Key features

- **Mainstream, Entry Appliance, Low Power, Cost effective**
- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C236 chipset
- 2 Fixed 3.5" drive bay or 3x 2.5" drive option
- Up to 64GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slots
- 1 PCI-E 3.0 x8 AOC slot
- 2 GbE ports with Intel® i210-AT 1 shared IPMI port
- 1 VGA, 1 COM, 2 USB 2.0, 2 USB 3.0
- 350W Platinum Level power supply



Processor/Cache	
Processor	Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series
Chipset	
Chipset	Intel® C236 chipset
System Memory	
Memory Capacity	4x 288-pin DDR4 DIMM slots, Up to 64GB DDR4 ECC UDIMM
Expansion Slots	
PCI-Express	1 PCI-E 3.0 x8 AOC slot, 1 M.2 connector
Integrated On-Board	
SATA	SATA3 (6Gbps) via C236 controller, RAID 0, 1, 5, 10 support
LAN	2 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 Shared IPMI LAN port
Add-on Options	
Raid Card	Optional
Optical Drive	Optional

Front Panel	
LED Indicators	Power LED, Hard drive activity LED, 2 Network activity LEDs, System Overheat LED, Information LED (temp., status)
Buttons	Power On/Off button, System Reset Button
Drive Bays	
HDD Bays	2x 3.5" or 3x 2.5" (option) internal drive bays
Power Supply	
350W Platinum Level power supply	
Cooling System	
2x 4cm counter-rotating mid fans	
Form Factor	
Form Factor	1U Rackmount
Height	: 1.7" (43mm),
Width	: 17.2" (437mm),
Depth	: 14.4" (366mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	