

Tyrone Camarero Specifications

Camarero SS4C0TR-55WR Key features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™i5/Core™i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100/E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
- Intel® C246
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1, 2 PCI-Ex16 slots are running at NA/16, or 8/8, 1 - 5V PCI 32bit, M.2 Interface: 2 PCI-E 3.0 x4, M.2 Form Factor: 2242/2260/2280/22110, M.2 Key: M-Key, M.2#1 are shared with PCI-Ex4 slot, M.2#2 is shared with U.2, U.2 Interface: 1 PCI-E 3.0 x4
- 1 HDMI port, 1 DVI - D port, 1 DP (DisplayPort) port, Intel UHD P630 graphic(For CPU Xeon E-21XXG series only)
- Intel® C246 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with Intel® Ethernet Controller I210-AT, Single LAN with Intel® PHY I219LM LAN controller Support vPro, Single LAN with Gigabit LAN WiFi + Bluetooth 5.0
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
- 550/1200 Redundant Power Supply, 80 Plus Platinum
- Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan



Processor/Cache

Processor	8th/9th Generation Intel® Core™ i9/Core™ i7/Core™i5/Core™i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100/E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
-----------	--

Chipset

Chipset	Intel® C246
---------	-------------

System Memory

Memory Capacity	Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
-----------------	---

Expansion Slots

PCI-Express	1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1, 2 PCI-Ex16 slots are running at NA/16, or 8/8, 1 - 5V PCI 32bit, M.2 Interface: 2 PCI-E 3.0 x4, M.2 Form Factor: 2242/2260/2280/22110, M.2 Key: M-Key, M.2#1 are shared with PCI-Ex4 slot, M.2#2 is shared with U.2, U.2 Interface: 1 PCI-E 3.0 x4
-------------	--

Integrated On-Board

SATA	Intel® C246 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
LAN	2 1GbE LAN ports

Add-on Options

Raid Card	Optional
Optical Drive	None

Front Panel

LED	Front Control Panel Power Switch, System Reset
Buttons	Power On/Off button

Drive Bays

HDD Drives	External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
Peripheral Drives	None

Power Supply

550/1200 Redundant Power Supply, 80 Plus Platinum

Cooling System

Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
--

Form Factor

Form Factor	Tower/Convertible/5U Rackmount
Dimensions	560 x 200 x 430 mm (22" x 7.9" x 16.9")

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com