

Tyrone Camarero Specifications

Camarero SS4Z0TR-55L

Key features

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core i7/i5/ i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C236 chipset
- Up to 64GB DDR4 2400MHz ECC/Non-ECC Unbuffered UDIMM; 4 DIMM slots
- 1 PCI-E 3.0 x16 (in x16), 2 PCI-E 3.0 x4 (in x8)
- Dual GbE LAN w/ Intel i219LM + i210AT
- 2 DP, 1 DVI-I, 3 independent displays via Intel HD Graphics, VGA port for BMC
- 4 SATA3 (6Gbps) via C236; RAID 0, 1, 5, 10
- I/O: 1 SATA DOM, 2 COM, TPM 1.2 header, ALC 888S HD Audio
- IPMI, AMT vPro
- Supports 12V DC power input
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5
- Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 500/1200W Single PS, 80Plus Platinum

Tyrone®



Processor/Cache

Processor Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core i7/i5/ i3 series, Intel® Celeron® and Intel® Pentium®

Chipset

Chipset Intel® C236 chipset

System Memory

Memory Capacity Up to 64GB DDR4 2400MHz ECC/Non-ECC Unbuffered UDIMM; 4 DIMM slots

Expansion Slots

PCI-Express 1 PCI-E 3.0 x16 (in x16), 2 PCI-E 3.0 x4 (in x8)

Integrated On-Board

SATA Intel® C236 controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10,Intel RSTe

LAN 2 RJ45 Ethernet LAN ports

Add-on Options

Raid Card Optional

Optical Drive None

Front Panel

LED Front Control Panel Power Switch, System Reset

Buttons Power On/Off button

Drive Bays

HDD Drives External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5

Power Supply

500/1200W Single PS, 80Plus Platinum

Cooling System

Front: 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan

Form Factor

Form Factor 5U Rackmount

Dimension : 560 x 200 x 430 mm (22" x 7.9" x 16.9")

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com