

# Tyrone Camarero Specifications



## Camarero SSA200A2W-212

### Key features

- Web Server, Firewall ApplicationData Center Optimized, Value IaaS Cloud Computing, Compact Server DNS & Gateway Servers, Firewall Application CDN, Edge Nodes
- Single 4th Generation AMD EPYC™ 9004 Series Processors
- 12 DIMM slots up to 3TB 3DS ECC RDIMM DDR5-4800MHz
- 2 PCI-E 5.0 x16 FHFL, 2 PCI-E 5.0 x16 FHHL
- Dual AIOM with NCSI (OCP 3.0) for networking, 1 dedicated IPMI LAN
- 12x 3.5/2.5" hot-swap hybrid NVMe/SATA/SAS drive bays
- 3 heavy duty fans with optimal fan speed control, 1 air shroud
- 1200W redundant Titanium level 100-240Vac and 200-240 Vdc power supplies, (\*Full redundancy based on configuration and application load)
- 2 On-board PCI-E 3.0 x2 M.2 NVMe 80mm/110mm (Boot)



### Processor/Cache

Processor Single 4th Generation AMD EPYC™ 9004 Series Processors

### Chipset

Chipset System On Chip

### System Memory

Memory Capacity 12 DIMM slots up to 3TB 3DS ECC RDIMM DDR5-4800MHz

### Expansion Slots

PCI-Express 2 PCI-E 5.0 x16 FHFL, 2 PCI-E 5.0 x16 FHHL

### Integrated Onboard

LAN LAN : 1 Dedicated IPMI LAN port

### Add-on Options

Raid Card: Optional  
Optical Drive: None

### Front Panel

LEDs Drive activity, Network activity, Power status, Universal Information (UID)

Buttons Power On/Off, UID button

### Drive Bays

HDD Bays 12x 3.5/2.5" hot-swap hybrid NVMe/SATA/SAS drive bays

### Power Supply

1200W redundant Titanium level 100-240Vac and 200-240 Vdc power supplies, (\*Full redundancy based on configuration and application load)

### Form Factor

Form Factor 2U Rackmount

Dimensions: Height - 3.5" (89mm),  
Width - 17.2" (437mm),  
Depth - 25.5" (648mm)

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit

[www.tyronesystems.com](http://www.tyronesystems.com)