

Tyrone Camarero Specifications

Tyrone

Camarero: SSA200C3A-28

Key Feature

Designed for financial companies, AMD Xilinx Solarflare X2 and X3 Ethernet adapters validated



- AMD Ryzen™ 7000 Series LGA1718 up to 170W TDP Processors
- 4x DDR5 UDIMM Slots, ECC/Non-ECC DDR5-5200 Up to total 128GB
- 2x PCIe 5.0 x16 (FHHL) slots (16/NA or 8/8)
- 2x 1GbE LAN (Intel® I210-AT) IPMI 2.0 + KVM with Dedicated LAN (1GbE)
- 4x 3.5" SATA drive bays (or up to 8x 3.5"/2.5" SATA/SAS drive bays via optional RAID AOC) M.2 : 2x NVMe (PCIe 5.0x4)
- 3x 80mm Fan(s)
- 800W Redundant Titanium Level power supplies

Processor/Cache	
Processor	AMD Ryzen™ 7000 Series LGA1718 up to 170W TDP Processors
System Memory	
Memory Capacity	4x DDR5 UDIMM Slots, ECC/Non-ECC DDR5-5200 Up to total 128GB
Chipset	
Chipset	AMD B650
Expansion Slot	
PCI-Express	2 PCIe 5.0 x16 slot(s), 1 PCIe 4.0 x4 slot(s)
Integrated Onboard:	
SATA	4 SATA (6Gbps) port(s)
Network Connectivity	1x 1GbE BaseT with Realtek RTL8211F PHY (dedicated IPMI), 2x 1GbE BaseT with Intel® I210-AT
Add-on Options	
Raid Card	Optional
Optical Drive	None

Front Panel	
LED	HDD activity LED, Network Activity LEDs, Power Fail LED, Power status LED, System Information LED
Buttons	Power On/Off button, System Reset button
Drive bays	
HDD Bays	4x 3.5" SATA drive bays (or up to 8x 3.5"/2.5" SATA/SAS drive bays via optional RAID AOC) M.2 : 2x NVMe (PCIe 5.0x4)
Power Supply	
Power Supply	800W Redundant Titanium Level power supplies
Cooling System	
Fans	3x 80mm Fan(s)
Form Factor	
Form Factor	2U Rackmount
Dimensions	
Dimensions	Height : 3.5" (89mm), Width : 17.2" (437mm), Depth : 25.5" (647mm)
<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit www.tyronesystems.com</p>	