Tyrone Camarero Specifications

Camarero-SSA200F0A-310

Kev Feature

- AMD Ryzen™ 7000 series Processors, single socket LGA-1718 (socket AM5) supported, TDP supports up to 170W.
- Up to 192GB ECC/non-ECC Unbuffered DIMM, DDR5-5200MHz, in 4 DIMM slots
- "2 PCIe 5.0 x16 (16/NA or 8/8), support up to 2 GPU cards(mechanical is up to 1 triple-width GPU card or 2 double-width GPU cards)
- 1 PCle 4.0 x4"
- 2x 1Gbit LAN port(i210 AT); a dedicated Realtek 1Gbit LAN for IPMI.
- Micro-ATX form factor
- 1 USB 3.2 Gen2x2 ports (type C, 20Gb, rear); 5 USB 3.2 Gen2 ports(2 Type C, rear, support DP 1.4 Alt mode)
- 1 HDMI 2.0 port, 1 DP 1.4a port
- M.2 Interface: 2 PCle 5.0 x4 (RAID 0 & 1), M.2 Form Factor: 2280/22110, M.2 Key: M-Key
- 4x 2.5" fixed drive bay, 6x 3.5" fixed drive bay
- 1x 12cm rear exhaust fan(s), 2x 12cm front cooling fan(s)
- 750W 80PLUS Gold Fully-Modular Power Supply







Processor/	Caci	ne

Processor AMD Ryzen™ 7000 series Processors, single

socket LGA-1718 (socket AM5) supported, TDP supports up to 170W.

System Memory

Memory Capacity Up to 192GB ECC/non-ECC Unbuffered DIMM, DDR5-5200MHz, in 4 DIMM slots

Chipset

Chipset

B650

Expansion Slot

PCI-Express

"1 PCIe 4.0 x4,2 PCIe 5.0 x16 slots (16/NA or 8/8), M.2 Interface: 2 PCle 5.0 x4, RAID 0 & 1"

Integrated Onboard:

Network Connectivity Dual LAN with Intel® i210 Gigabit Ethernet Controller, Single LAN with ASPEED AST2600

BMC, Dedicated LAN for IPMI

SATA:

4 SATA3 ports; RAID 0,1,5,1

Add-on Options

Raid Card

Optional

Optical Drive

Optional

• Intel	the Intel logo,the Intel Inside logo,Xeor	n,and Intel Xeon Phi are trademarks	of Intel Corporation in the U.S a	and/Or other Countries
---------	---	-------------------------------------	-----------------------------------	------------------------

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners

Front Panel	
LED	HDD activity, Network activity, Power status, System information (overheat/UID
Buttons	Power On/Off button
Drive bays	
HDD Bays	4x 2.5" fixed drive bay, 6x 3.5" fixed drive bay

750W PS2 Multi-output Power Supply **Power Supply**

2x standard 5.25" drive bay

Cooling System

Periphheral

Power Supply

Bays

Fans 750W PS2 Multi-output Power Supply

Form Factor

Form Factor 3U Rackmount

Dimensions

Dimensions Height: 18.1" (460 mm), Width: 7.9"

(200 mm), Depth: 19.4" (493 mm)

Email: Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com