

Tyrone Camarero Specifications

Camarero SSA700TR-14RL

Key features



- **Web Hosting, VM, Cloud Computing, Connectivity/Storage, Computer Nodes**
- Single AMD EPYC™ 7001/7002* series Processor (*Board revision 2.x required) Socket SP3 Supports CPU TDP 225W / cTDP up to 240W Up to 32 Cores (Board revision 1.x + 7001 Processors), Up to 64 Cores (Board revision 2.x + 7002 Processors)
- System on Chip (SoC)
- 8 DIMM slots, Supports up to 1TB Registered ECC DDR4 2666MHz SDRAM (7001 Processors), Supports up to 2TB Registered ECC DDR4 3200MHz SDRAM (Board revision 2.x required + 7002 Processors), 8-channel memory bus DDR4 2666 MHz Registered ECC, 240-pin gold-plated DIMMs DDR4 3200 MHz Registered ECC, 240-pin gold-plated DIMMs (Board revision 2.x required + 7002 Processors)
- 1 PCI-E 3.0 x16 (FH/HL) slot
M.2 :Interface: PCI-E 3.0 x4 (NVMe based), Form Factor: 2280, 22110, Key: Onbard M-key, Number of M.2: Single
- 16 SATA3, 1 M.2
- Dual Gigabit Ethernet LAN Ports
- ASPEED AST2500 BMC graphics
- Up to 5 USB 3.0 ports (2 rear + 2 via header + 1 Type A), Up to 4 USB 2.0 ports, (2 rear + 2 via header)
- 7 PWM 4-pin Fans with tachometer status monitoring
- 4 x 3.5" hot-swap SAS/SATA
- 4 x 40x28mm PWM fan(s)
- 400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm

Processor/Cache	
Processor	Single AMD EPYC™ 7001/7002* series Processor (*Board revision 2.x required), Socket SP3, Up to 32 Cores, Up to 64 Cores (Board revision 2.x required)
Chipset	
Chipset	System on Chip (SoC)
System Memory	
Memory Capacity	8 DIMM slots, Supports up to 1TB Registered ECC DDR4 2666MHz SDRAM (7001 Processors), Supports up to 2TB Registered ECC DDR4 3200MHz SDRAM (Board revision 2.x required + 7002 Processors), 8-channel memory bus DDR4 2666 MHz Registered ECC, 240-pin gold-plated DIMMs DDR4 3200 MHz Registered ECC, 240-pin gold-plated DIMMs (Board revision 2.x required + 7002 Processors)
Expansion Slots	
PCI-Express	1 PCI-E 3.0 x16 (FH/HL) slot M.2 :Interface: PCI-E 3.0 x4 (NVMe based), Form Factor: 2280, 22110, Key: Onbard M-key, Number of M.2: Single
Integrated On-Board	
SATA	SATA3 (6 Gbps)
IPMI :	Support for Intelligent Platform Management Interface v.2.0, IPMI 2.0 with virtual media over LAN and KVM-over-LAN support, ASPEED AST2500 BMC
Network Controllers	2 1GbE LAN via Intel® I210, 1 Realtek RTL8211E PHY (dedicated IPMI)
Add-on Options	
Raid Card	Optional
Optical Drive	Optional

Front Panel	
LEDs :	2 Network Activity LEDs, HDD activity LED, Power Status LED, System Information LED
Buttons:	Power On/Off button, System Reset Button
USB :	5 USB 3.0 ports, (2 rear + 2 via header + 1 Type A), 4 USB 2.0 ports (2 rear + 2 via header)
LAN :	2 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 Dedicated IPMI LAN port
Drive Bays	
HDD Bays	4 x 3.5" hot-swap SAS/SATA
Peripheral Drives	Optional 1 x Slim DVD-ROM Drive, Optional 1 x USB + COM port tray
Power Supply	
	400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm
Cooling System	
	4 x 40x28mm PWM fan(s)
Form Factor	
Form Factor	1U Rackmount
Height :	1.7" (43 mm)
Width :	17.2" (437 mm) ,
Depth :	19.85" (503 mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	

AMD the AMD logo are trademarks of Advanced Micro Devices in USA and/or other countries
 Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners