

Tyrone Camarero Specifications

Camarero SSC40TR-34L

Key features

Entry-Level Server for SOHO, SMB Remote access for mobile users Data sharing/storage and Centralized backup

- Single Socket H4 (LGA 1151), CPU TDP support up to 95W Support Intel® Xeon® processor E-2100 / E-2200 series, 8th Gen. Intel® Core™ i3 Processors, Intel® Celeron®, Intel® Pentium®
- Intel® C242 chipset
- Memory Capacity : 4 DIMM slots Up to 128GB ECC UDIMM, Up to DDR4-2666MHz, Memory Type : 2666/2400/2133MHz ECC DDR4 SDRAM DIMM Sizes :32GB, 16GB, 8GB
Note: Future support for 128GB via BIOS update expected in early 2019
- 1 PCI-E 3.0 x8 (in x16) slot, 2 PCI-E 3.0 x4 (in x8) slots, M.2 Interface: 1 PCI-E 3.0 x4 , M.2 Form Factor: 22110/2280, M.2 Key: M-Key
- 4 internal 3.5" drive bays, 2 external 5.25" peripheral bays
- 2 USB 3.1 Gen1 (front), 2 USB 3.1 Gen1 (rear), 2 USB 2.0 (rear)
- 1 COM port, 1 VGA port Power Supply
- 1x 9cm (rear) PWM fan w/ tool-less design Optional 1x 8cm (front) cooling fan
- 400W Gold Certified High Efficient Power Supply



Processor/Cache

Processor	Single Socket H4 (LGA 1151), CPU TDP support up to 95W Support Intel® Xeon® processor E-2100 / E-2200 series, 8th Gen. Intel® Core™ i3 Processors, Intel® Celeron®, Intel® Pentium®
-----------	---

Chipset

Chipset	Intel® C242 chipset
---------	---------------------

System Memory

Memory Capacity	Memory Capacity : 4 DIMM slots Up to 128GB ECC UDIMM, Up to DDR4-2666MHz, Memory Type : 2666/2400/2133MHz ECC DDR4 SDRAM DIMM Sizes :32GB, 16GB, 8GB
-----------------	--

Note: Future support for 128GB via BIOS update expected in early 2019

Expansion Slots

PCI Express	1 PCI-E 3.0 x8 (in x16) slot, 2 PCI-E 3.0 x4 (in x8) slots, M.2 Interface: 1 PCI-E 3.0 x4 , M.2 Form Factor: 22110/2280, M.2 Key: M-Key
-------------	--

Integrated On-Board

SATA	SATA3 (6Gbps) via Intel C242 controller, RAID 0, 1, 5, 10 support
LAN	2 RJ45 Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Card	Optional
Optical Drive	Optional

Front Panel

LED	Power LED, Hard drive activity LED, Network activity LEDs, System Information LED
Ports	2 USB 3.1 Gen 1 ports
Buttons	Power On/Off button.

Drive Bays

HDD Drives	4 Fixed 3.5" drive bays
Peripheral Drives	2 External 5.25" Peripheral bays

Power Supply

400W Gold Certified High Efficient Power Supply

Cooling System

1x 9cm (rear) PWM fan w/ tool-less design
Optional 1x 8cm (front) cooling fan

Form Factor

Mid Tower	
Dimensions:	Height : 14.25" (362mm), Width : 7.25" (184mm), Depth : 16.75" (425mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com