

Tyrone Camarero Specifications

Camarero- SSI10F0A-34

Key Feature

High-performance Gaming, Content Creation

- Single Socket V (LGA-1700), 14th/13th/12th Gen Intel® Core™ i9/i7/i5/i3, Pentium® and Celeron® Processors
- 2 PCIe 5.0 x16 slots (16/NA or 8/8)
- Single LAN with Intel® i219V 1Gb Single LAN with Marvell AQC113 10Gb
- 3x 12cm PWM Fans
- 750W PS2 Multi-output Power Supply



Processor/Cache		Front Panel	
Processor	Single Socket V (LGA-1700), 14th/13th/12th Gen Intel® Core™ i9/i7/i5/i3, Pentium® and Celeron® Processors	LED	HDD activity Power On
Chipset	Intel Z790	Buttons	Power On/Off
System Memory		Drive bays	
Memory Capacity	4 DIMM slots Up to 128GB: 4x 32 GB DRAM Memory Type: 4400MHz DDR5 non-ECC UDIMM	Drive bays	6x 3.5" SATA drive bays M.2 1x PCIe 4.0 x4 2x PCIe 3.0 x4
Expansion Slots		Peripheral Bays	2x 5.25" drive bays
PCI-Express	2 PCIe 5.0 x16 slot(s) 2 PCIe 3.0 x1 slot(s)	Power Supply	
Integrated On-Board		Power Supply	750W PS2 Multi-output Power Supply
SATA	6 SATA (6Gbps) port(s)	Cooling System	
Network Connectivity	1x 1GbE BaseT with Intel® PHY i219V 1x 10GbE BaseT with Marvell AQC113	Fans	1x 120mm Fan(s) 2x 120mm Fan(s)
Add-on Options		Form Factor	
Raid card	Optional	Form Factor	5U/ Mid-Tower
Optical Drive	Optional	Dimensions	
		Dimensions	(W x H x L) 150 x 86 x 140 mm
<p>Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com</p>			