

Tyrone Camarero Specifications

Tyrone

Camarero- SSI200C3R-48

Key Feature

- 4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E), CPU TDP supports up to 350W TDP
- Intel C741® Chipset
- Up to 2TB 3DS ECC RDIMM, DDR5-4800MT/s (1DPC) in 8 DIMM slots
- "3 PCIe 5.0 x8,2 PCIe 5.0 x16, M.2 Interface: 2 PCIe 5.0 x4, M.2 Form Factor: 2280, 22110
- Dual LAN with 1GbE with Intel® I210
- 4 USB 3.2 Gen1 (2 rear, 1 Type-A, 1 via header), 2 USB 2.0 (2 rear)
- Intel® C741 controller for 10 SATA3 (6 Gbps) ports
- 8x 3.5"/2.5" hot-swap SAS drive bay with SES3
- 2x 80mm PWM Rear Chassis Fans (9.4k RPM), 3x 80mm high-performance fan(s) (9.4k RPM)
- 1200W (1 + 1) Redundant Titanium Level Certified High-Efficiency Power Supply



Processor/Cache		Drive bays	
Processor	4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E), CPU TDP supports up to 350W TDP	HDD Bays	8x 3.5"/2.5" SAS3/SATA3 Backplane for Hot-Swappable Drives
System Memory		Peripheral Bays	3x standard 5.25" drive bay
Memory Capacity	Up to 2TB 3DS ECC RDIMM, DDR5-4800MT/s (1DPC) in 8 DIMM slots	Power Supply	
Chipset		Power Supply	1200W (1 + 1) Redundant Titanium Level Certified High-Efficiency Power Supply
Chipset	Intel C741® Chipset	Cooling System	
Expansion Slot		Fans	2x 80mm PWM Rear Chassis Fans (9.4k RPM), 3x 80mm high-performance fan(s) (9.4k RPM)
PCI-Express	"3 PCIe 5.0 x8,2 PCIe 5.0 x16, M.2 Interface: 2 PCIe 5.0 x4, M.2 Form Factor: 2280, 22110"	Form Factor	
Integrated Onboard:		Form Factor	4U Rackmount
SATA	10 SATA3 (6Gbps) port(s)	Dimensions	
LAN	2 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 Dedicated IPMI LAN port	Dimensions	Dimensions: Height : 17.8" (452mm), Width : 7" (178mm), Depth : 25.5" (647mm)
Add-on Options		<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit www.tyronesystems.com</p>	
Raid Card	Optional		
Optical Drive	Optional		