

Tyrone Camarero Specifications

Camarero- SSI200F0A-34

Key Feature

2D/3D Content Creation, VR Content Development

- Socket E (LGA4677) support Intel® Xeon® W-2400 processors
- Intel® W790
- 8 DIMMs
- 1x 1GbBaseT, 1x 10GbBaseT
- 4 3.5" SATA3 drive bays; ; 2 M.2 NVMe
- 1 120 mm Fan(s) ; 1 120 mm Fan(s)
- 1200W Power Supplies Platinum Level (92%+)



Processor/Cache	
Processor	Single Socket E (LGA4677) Intel® Xeon® W-2400 processors
Chipset	
Chipset	Intel® W790
System Memory	
Memory Capacity	Memory Capacity: 8 DIMM slots Up to 1TB; 8x 128 GB DRAM Memory Type: 4800MHz ECC DDR5 RDIMM / LRDIMM
Expansion Slots	
PCI-Express	1 PCIe 4.0 x4 slot(s) 3 PCIe 5.0 x16 slot(s)
Integrated On-Board	
IPMI	upport for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Network Connectivity	1x 10GbE BaseT with Marvell AQC113, 1x 1GbE BaseT with Intel® I210-AT

Front Panel	
LED	HDD activity LED
Buttons	Power On/Off button
Drive bays	
Drive bays	4x 3.5" SATA drive bays, M.2 2x PCIe 5.0 x4.
Peripheral Bays	2x 5.25" drive bays
Power Supply	
Power Supply	1200W PS2 Multi-output power supply
Cooling System	
Fans	1x 120mm Fan(s), 1x 120mm Fan(s), 1x 120mm Fan(s) (optional), 1x 120mm Fan(s) (optional)
Form Factor	
Form Factor	5U/ Mid Tower
Dimensions	
Dimensions	(W x H x L) 150 x 86 x 185 mm
<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit</p> <p>www.tyronesystems.com</p>	