

Tyrone Camarero Specifications

Camarero SSi00TR-45TR

Key features

- Intel® 8th/9th Generation Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® series Processor, Single Socket LGA 1151 supported, CPU TDP support Up to 140W
- Intel® Z390 Express
- Up to 64GB Unbuffered non-ECC UDIMM, in 4 DIMM slots (Limited to Gen 8th series and Gen 9th core i3, Pentium and Celeron) Up to 128GB Unbuffered non-ECC UDIMM, in 4 DIMM slots (Limited to Gen 9th core i5/i7/i9)
- 4 PCI-E 3.0 x16 slots (16/NA/16/NA or 16/NA/8/8 or 8/8/16/NA or 8/8/8/8), 1 PCI-E 3.0 x1, M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1 and 1 CNVi
M.2 Form Factor: 2260/2280/22110, 2260/2280, 2230, M.2 Key: M-Key, M-Key, E-Key (RAID 0,1 support)
M.2-M1 port shares PCI-E link with U2-1 port; M.2-M2 port shares link with SATA port4 and port5; M.2-E1 port pre-installed one 802.11ac WiFi+BT5.0 module
U.2 Interface: 2 PCI-E 3.0 x4 and PCI-E 3.0 x4"
- 2 DP (DisplayPort) ports, 1 HDMI port, Display port up to 1.2, HDMI up to 2.0a
- Intel® Z390 Express controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with Intel® single Ethernet PHY i219V, Single LAN with Aquantia® AQC107 10G Ethernet Controller
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
- 120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 550/1200W Redundant power supply , 80Plus Platinum



Processor/Cache	
Processor	Intel® 8th/9th Generation Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® series Processor, Single Socket LGA 1151 supported, CPU TDP support Up to 140W
Chipset	
Chipset	Intel® Z390 Express
System Memory	
Memory Capacity	Up to 64GB Unbuffered non-ECC UDIMM, in 4 DIMM slots (Limited to Gen 8th series and Gen 9th core i3, Pentium and Celeron) Up to 128GB Unbuffered non-ECC UDIMM, in 4 DIMM slots (Limited to Gen 9th core i5/i7/i9)
Expansion Slots	
PCI-Express	4 PCI-E 3.0 x16 slots (16/NA/16/NA or 16/NA/8/8 or 8/8/16/NA or 8/8/8/8), 1 PCI-E 3.0 x1, 2 M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1 and 1 CNVi, Form Factor: 2260/2280/22110, 2260/2280, 2230, Key: M-Key, M-Key, E-Key (RAID 0,1 support) M.2-M1 port shares PCI-E link with U2-1 port; M.2-M2 port shares link with SATA port4 and port5; M.2-E1 port pre-installed one 802.11ac WiFi+BT5.0 module
Integrated On-Board	
SATA:	Intel® Z390 Express controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
Network Controllers:	Single LAN with Intel® single Ethernet PHY i219V, Single LAN with Aquantia® AQC107 10G Ethernet Controller
Add-on Options	
Raid Card	Optional
Optical Drive	None

Front Panel	
Power Switch, System Reset, USB 3.0 x 2	
Drive Bays	
External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5	
Power Supply	
550/1200W Redundant power supply , 80Plus Platinum	
Cooling System	
120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan	
Form Factor	
Form Factor	5U Rackmount
Dimension: 12.1" x 9.6" (30.48cm x 24.38cm)	
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	

© Intel, the Intel logo, the Intel Inside logo, Xeon and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and /or Other Countries.
 © Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners