# **Tyrone Camarero Specifications**

Camarero SS400TR-14

# **Key features**

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series,Intel® Celeron® and Intel® Pentium®
- Intel® C236 chipset
- 4x 3.5" Hot-swap SATA3 bays w/ RAID
- Up to 64GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slots
- 1 PCI-E 3.0 x8 (in x16) AOC slot
- 2x GbE ports with Intel® i210-AT
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- I/O ports: 1x VGA, 2x COM, 2x USB 3.0 (front/rear), USB 2.0
- 350W Platinum Level Power Supply









# Processor/Cache

Processor Single socket H4 (LGA 1151) supports

Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®

# Chipset

Chipset Intel® C236 chipset

#### **System Memory**

Memory Capacity Up to 64GB Unbuffered ECC UDIMM

DDR4 2400MHz; 4 DIMM slots

# **Expansion Slots**

PCI Express 1x PCI-E 3.0 x8 (in x16) AOC slot,

1x M.2 connector

# **Integrated On-Board**

SATA SATA3 (6Gbps) via C236 controller,

RAID 0, 1, 5, 10 support

LAN 2x RJ45 Gigabit Ethernet LAN ports,

1x RJ45 Dedicated IPMI LAN port

#### **Add-on Options**

Raid Card Optional

Optical Drive Optional

#### **Front Panel**

Front Panel Power LED, Hard drive activity LED,

2x Network activity LEDs, System Overheat LED

Buttons Power On/Off button. Reset button

# **Drive Bays**

HDD Bays 4x 3.5" Hot-swap SATA3 drive bays

Optional 2x 2.5" Fixed drives internal

# **Power Supply**

350W Platinum Level Power Supply

# **Cooling System**

4x 40x28mm 4-pin PWM Cooling Fans

#### **Form Factor**

Form Factor 1U Rackmount

Width: 17.2" (437mm), Height: 1.7" (43mm), Depth: 19.8" (503mm)

Email: info@tyronesystems.com For more/current product information, visit

www.tyronesystems.com