Tyrone Camarero Specifications

Tyrone

Camarero SS400TR-14RL

Key features

- Web Hosting, VM, Compact Network Appliance
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 165W
- Intel ®C621 chipset
- 4 Hot-swap 3.5" SATA3 bays w/ RAID
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
- 1 PCI-E 3.0 x16 slot (FH, HL)
- 2x 1GbE with Marvell ® 88E1512
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 1 VGA, 2 COM, 5 USB 3.0, 6 USB 2.0
- 400W Redundant Platinum Power Supplies w/ BBP® option

Processor/Cache

Add-on Options

Raid Card

Optical Drive

Processor/Cache	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 165W
Chipset	
Chipset	Intel [®] C621 chipset
System Memory	
Memory Capacity	Up to 1.5TB 3DS ECC RDIMM, DDR4- 2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots;Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
Expansion Slots	
PCI-Express	1 PCI-E 3.0 x16 slot (FH, HL)
Integrated On-Board	
SATA	SATA3 (6Gbps) via C621 controller RAID 0, 1, 5, 10 support
LAN	2 RJ45 1GbE LAN ports,





Front Panel		
LED Indicators	Power LED, Hard drive activity LED, Network activity LEDs, System Overheat LED	
Buttons	Power On/Off button, System Reset button	
Drive Bays		
HDD Bays	4 Hot-swap 3.5" SATA3 drive bays.	
M.2	Interface: PCIe 3.0 x4, Form Factor: 2242, 2280	
Peripheral Drives	1 Slim DVD-ROM drive, 1 USB + COM port tray	
Power Supply		
400W Redundant Platinum Power Supplies w/ BBP [®] option		
Cooling System		
4x 40x28mm PWM fans; 2x fans for AOC cooling. Optional 2 fans for AOC cooling		
Form Factor		
Form Factor	1U Rackmount	
Height : Width : Depth :	1.7" (43mm), 17.2" (437mm), 19.8" (503mm)	

Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com

0 Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries 0 Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners

1 RJ45 Dedicated IPMI LAN port

Optional

Optional