Tyrone VERTA

Verta D2-SJC-424S



Simplicity and flexibility to scale.

The era of having multiple units for different storage needs is passing, as diverse storage products prevent optimum utilization and can be difficult to manage. Verta series from Tyrone Systems, consolidates all your storage requirements.

Features	Detailed Specifications
Form Factor	4U JBOD chassis
Controller	Single Controller
Bays	24 x 3.5" hot-swappable HDDs bays
Power Supply Unit	1000W Titanium level power supplies
System Cooling (per node)	5 hot-plug redundant cooling fans
Drive Interface	SAS
Supported Drives	SAS/SATA LFF/SFF HDDs/SSDs
Environmental Specifications	Operating temp: 5°C ~35°C / Non Operating temp: -40°C~ 70°C / Operating Relative humidity: 8%~90%
Packaging Size (W x D x H)	27" (686 mm) x 14.8" (376 mm) x 37.3" (947 mm)
Weight (without HDDs)	32.00 kg
Mounting	Standard: 28" slide rail

^{1:} The protocols are interface specific and not all protocols work with all interfaces_e.g. FC target requires FC ports. Not all protocol options are available for all clients e.g. SRP is not available for MAC OS.

^{3:} SSD acceleration uses up to 4 HDD bays for populating SSDs reducing the number of available bays.



For enquiries reach us at: Email: info@tyronesystems.com | www.tyronesystems.com

CONNECT WITH US

- facebook.com/tyronesystems
- twitter.com/tyronesystems
- blog/tyronesystems.com
- youtube.com/tyronesystems

^{2:} Not all host interfaces combinations are available. For e.g. it is not possible to have 12 Gigabit ports + 4 10G ports in the same unit.