

The era of having multiple units for different storage needs is passing, as diverse storage products prevent optimum utilization and can be difficult to manage. Verta series from Tyrone Systems, consolidates all your storage requirements.

Features	Detailed Specifications
Form Factor	4U JBOD storage chassis
Controller	Dual Controller
Bays	90 x 3.5" hot-swappable HDDs bays
Power Supply Unit	1000W High-Efficiency Redundant Power Supply
System Cooling (per node)	5x 80mm heavy duty fan(s) with PWM fan(s) speed control
Drive Interface	SAS
Supported Drives	SAS/SATA LFF/SFF HDDs/SSDs
Environmental Specifications	Operating temp: 5°C ~35°C / Non Operating temp: -40°C~ 70°C / Operating Relative humidity: 8%~90%
Packaging Size (W x D x H)	31.49" (800 mm) x 30.12" (765 mm) x 45.28" (1150 mm)
Weight (without HDDs)	107.00 kg
Mounting	Standard: 28" slide rail

1: The protocols are interface specific and not all protocols work with all interfaces_e.g. FC target requires FC ports. Not all protocol options are available for all clients e.g. SRP is not available for MAC OS. 2: Not all host interfaces combinations are available. For e.g. it is not possible to have 12 Gigabit ports + 4 10G ports in the same unit. 3: SSD acceleration uses up to 4 HDD bays for populating SSDs reducing the number of available bays.



For enquiries reach us at: Email: info@tyronesystems.com | www.tyronesystems.com **CONNECT WITH US**

facebook.com/tyronesystems

Stwitter.com/tyronesystems

blog/tyronesystems.com

youtube.com/tyronesystems