

Tyrone Camarero Specifications

Tyrone

Camerero: ADI200F0A-48

Key Feature

- 4th/5th Gen Intel® Xeon Dual Processor
- 16 x DDR5 5600/4800MHz RDIMM(1 DPC) , Support up to 4TB(3DS RDIMM)
- 5 x16 PCIe5.0 , 1 x8 PCIe5.0 , 3 x8 MCIO PCIe5.0
- 2 x SATA3.0 (6 Gb/s) 7pin connectors, 1 x Slimline connector (up to 8 SATA ports)
- 1 x RJ45 GbE connector for BMC dedicate management port
- 2 x Broadcom BCM5720 based 1GbE
- 2 x USB3.1 Gen1 double stack type-A connector at rear I/O, USB 3.0 Gen1 on Front side
- 8 x 3.5"/2.5"(SATA) Fixed disks
- 1200W/1600W/2000W Power Supply



Processor/Cache	Drive bays
Processor 4th/5th Gen Intel® Xeon Dual Processor	HDD Bays 8 x 3.5"/2.5"(SATA) Fixed disks
System Memory	Power Supply
Memory Capacity 16 x DDR5 5600/4800MHz RDIMM(1 DPC) , Support up to 4TB(3DS RDIMM)	Power Supply 1200W/1600W/2000W Power Supply
Expansion Slot	Form Factor
PCI-Express 5 x16 PCIe5.0 , 1 x8 PCIe5.0 , 3 x8 MCIO PCIe5.0, 2 x M.2 2280 PCIe Gen4.0 x4 (Onboard)	Form Factor 4U Rackmount
Integrated Onboard:	Dimensions
SAS/SATA Storage 2 x SATA3.0 (6 Gb/s) 7pin connectors, 1 x Slimline connector (up to 8 SATA ports)	Dimensions 680 x 438 x 175 mm
Front Panel	Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com
Front I/O Ports 1 x Power Button, 1 x Reset Button, 2 x USB 3.0, 1 x System Power LED Button	
Rear I/O Ports 2 x 1000Base-T Ethernet Ports, 1 x 1000Base-T Dedicated Server Management Port, 2 x USB 3.1 Gen1 Type-A Port, 1 x DB-15 VGA connector, 1 x UID LED Button, 1 x External UID/switch button	