

Tyrone Camarero Specifications

Tyrone

Camarero: ADI300A3R-28

Key Feature

- Supports Dual Intel® Xeon® 6th Gen 6500/6700 processors
- Supports 8+8 DDR5 RDIMM Expandable Memory
- 6 x16 PCIe 5.0 Expansion Slots
- Latest AST2600 BMC Controller iKVM, vMedia support
- Support 8 x 3.5"/2.5" Hot Swappable Bays
- Dual 1GbE(RJ45) by Broadcom BCM5720
- Multiple PSU Options 800W/1300W/1600W 80+ CRPS



Processor/Cache	
Processor	Supports Dual Intel Xeon 6th Gen 6500/6700 Series CPUs of TDP upto 350W (FCLGA 4710)
System Memory	
Memory Capacity	Supports 8+8 DDR5 RDIMM Expandable Memory, Max Frequency 6400MHz Max Capacity 64GB/DIMM, Max System Memory 1TB
Expansion Slot	
PCI-Express	6 x16 PCIe5.0 / CXL2.0
Ports	
Ports	1 x RJ45 (RTL8211E) GbE connector for BMC dedicate management port (Rear) 2 x 1GbE (RJ45) by Broadcom BCM5720 (Rear) 2 x USB 3.0 Type A Ports (Front) 2 x USB 3.0 Type A Ports (Rear) 1 x DB-15 VGA connector (Rear) 1 x External UID/switch button (Rear)
Drive bays	
HDD Bays	Supports 8 x (SAS/SATA) 2.5"/3.5" Hot Swappable Bays 2 x M.2 2280 PCIe 5.0 x4 (Onboard) 2 x 2.5" Internal SATA Drives 1 x Slim DVD-ROM
Front LEDs	
Front LEDs	1 x Power LED Button 1 x Alert LED 1 x HDD Activity 2 x LAN Activity 1 x Reset Button 1x UID LED Button
Power Supply	
Power Supply	800W/1300W/1600W 80+ CRPS
Security	
Security	Chassis intrusion TPM 2.0
Form Factor	
Form Factor	2U Rackmount
Dimensions	
Dimensions	680 x 430 x 88 mm
<p>Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com</p>	