# **Tyrone Camarero Specifications**

# Camarero: ADI300A3S-436

# **Key Feature**

The ADI300A3S-436 Storage Server is designed for scalable, high-throughput storage deployments in data center and edge environments. It supports modular expansion, Intel's 6th Gen based dual CPUs, and flexible I/O fabrics to deliver predictable performance at scale. Leveraging state-of-the-art PCIe Gen5 integration and multi-tier storage architecture, the system enables seamless scaling from capacity-centric workloads to latency-sensitive access patterns.

- Supports Dual Intel® Xeon® 6th Gen 6500/6700 processors
- Supports 8+8 DDR5 RDIMM Expandable Memory
- 6 x16 PCIe 5.0 Expansion Slots
- Latest AST2600 BMC Controller iKVM, vMedia support
- Support 36 x 2.5"/3.5" Data drives + 2 x 2.5" hot-swap OS drives
- Dual 1GbE(RJ45) by Broadcom BCM5720
- 1300W 80+ Titanium Redundant Power Supply











#### **Processor**

**Processor** Supports Dual Intel Xeon 6th Gen

6500/6700 Series CPUs of TDP upto

300W (FCLGA 4710)

## **System Memory**

Capacity

Memory Supports 8+8 DDR5 RDIMM

Expandable Memory, Max Frequency 6400MHz

Max Capacity 256GB/DIMM, Max System Memory 4TB(3DS RDIMM)

## **Expansion Slot**

PCI-Express 6 x16 PCle5.0 / CXL2.0 (HHFL)

#### **Ports**

Ports 1 x RJ45 GbE connector for BMC

dedicate management port

(RTL8211E)

2 x 1GbE (RJ45) by Broadcom

BCM5720

2 x USB 3.0 Type A Ports (Front) 2 x USB 3.0 Type A Ports (Rear) 1 x DB-15 VGA connector 1 x external UID/switch button

#### **Environment**

**Temperature** Operating Temperature : 10°C ~ 35°C

Non Operating Temperature: 40°C ~

70°C

**Humidity** Non operation humidity: 20% ~ 90%

(Non-condensing)

#### Front Panel

**LED** 1 x Power LED Button

1x Alert LED

1 x HDD Activity LED 1 x LAN Activity LED 1 x Reset Button 1x UID LED Button

## Drive bays

**HDD Bays** Supports 36 x 2.5"/3.5" Hot Swappable

Bays (24Bay 12G + 12Bay 12G expander

controller based backplane)

Supports 2 x 2.5" hot-swap SATA OS

drives (7mm)

Supports 2 x M.2 2280 PCle Gen4.0 x4

(Onboard)

## **Power Supply**

Power Supply 1300W 80+ Titanium Redundant Power

Supply

## Security

Security TPM 2.0

# Form Factor

Form Factor 4U Rackmount

Gross Weight 42 Kg

**Dimensions** 680(L) x 430(W) x 174(H) mm

Email: Info@tyronesystems.com
For more/current product information, Visit
www.tyronesystems.com

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/Or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners