

Tyrone Lilliput Specifications



Lilliput D34010WYKH

- Intel® Visual BIOS
- Two SO-DIMM slots supporting up to 16 GB of 1600/1333 MHz 1.35V DDR3L memory
- Windows* 8.1 and 8 logo
- Compatible with Linux*
- VESA mount bracket (75 x 75mm and 100 x 100mm compatible)
- Half-length PCIe* mini-card slot
- Low-acoustics active cooling design
- Kensington lock support
- 3-year advanced warranty replacement
- 19V, 65W DC-DC power adapter



Processor/Cache

Processor 4th generation Intel® Core™ i3-4010U processor

System Memory

Memory Capacity Two SO-DIMM slots supporting up to 16 GB of 1600/1333 MHz 1.35V DDR3L memory

Expansion Slots

PCI-Express 1 x PCIe Mini Card Slot (Half Length),
1 x PCIe Mini Card Slot (Full Length)

Add-on Options

Audio Intel® HD Audio via Mini HDMI 1.4a, Mini Display Port 1.2 output supporting 8 channel(7.1) digital audio, Intel HD Audio via stereo analog audio jack (microphone in/headphone out/speaker out)

Graphics Intel® HD Graphics 4400, One Mini Display Port 1.2 supporting ultra-high definition 4K displays and multiple monitor functionality, One Mini HDMI 1.4a port

Storage Internal support for 2.5-inch HDD or SSD

Front Panel

Peripheral Connectivity Four super high-speed USB 3.0 ports (two back panel ports and two front ports)

Networking

Integrated Intel® PRO 10/100/1000 Network Connection, Wireless antennae (integrated into the chassis)

Power Supply

19V, 65W DC-DC power adapter

Form Factor

Form Factor Intel Mini ITX

Dimensions 116.6mm x 112mm x 51.5mm

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com