

Tyrone Camarero Specifications



Camarero DA400T3T-14i

Key features

- Two systems (nodes) in a 1U form factor & Cost-effective. Each node supports.
- Dual AMD Opteron™ 4000 Series Processors
- Up to 192 GB of Registered ECC DDR3-1600/1333/1066 in 12 DIMMs
- 920W High-efficiency Power Supply 80Plus Platinum Certified
- Mellanox ConnectX IB with single QSFP connector support
- 1 Low profile PCI- E Gen 2.0 x 16 Expansion Slots
- 2 x 3.5" Hot-swappable SATA Hard Drive bays
- 1 dedicated LAN for system Management



Processor/Cache	
Processor	Dual AMD Opteron™ 4000 Series
System Memory	
Memory Capacity	Twelve DIMM sockets up to 192GB Registered ECC or 64GB Unbuffered ECC/non-ECC DDR3 1600/1333/1066 SDRAM
Expansion Slots	
PCI-Express	1 Low profile PCI- E Gen 2.0 x 16 Expansion Slots
Integrated On-Board	
SATA	AMD SP5100 (RAID 0, 1)
LAN	2 RJ45 LAN ports 1 RJ45 Dedicated LAN supports IPMI
Add-on Options	
RAID card	Optional
Optical Drive	None

Front Panel :	
LED Indicators	Power LED,Hard drive activity LED,2x Network activity LEDs,System Overheat LED
Switches	Power On/Off Button,System Reset Button
Drive bays	
HDD bays	2 x 3.5" SATA hard drive bays
Peripheral Bays	None
Power Supply	
920W High-efficiency Power Supply 80Plus Platinum Certified	
Cooling System	
6x counter-rotating PWM fans w/ Optimal Fan Speed Control	
Form Factor	
1U Rack mount	
Height	1.7" (43mm)
Width	17.2" (437mm)
Depth	27.75" (705mm)

Email : info@tyronesystems.com
For more/current product information, visit
www.tyronesystems.com