

Tyrone Camarero Specifications



Camarero DA60037T-224R



Key features

Four hot-pluggable systems (nodes) in a 2U form factor.

Each node supports the following:

- Dual AMD Opteron™ 6000 series (6300P* ready) processors (Socket G34)
16/12/8/4-Core ready; HT3.0 Link Support
- Up to 256GB DDR3 1866MHz ECC Registered DIMMs; 8x DIMM sockets
- 1x Low-profile PCI-E 2.0 in x16 slot (For add-on card up to 6.59" in length)
- Dual-port GbE LAN Controller, 4x USB 2.0 ports, 1x dedicated LAN for system management (IPMI 2.0)
- LSI 6Gbps SAS 2108 w/ Hardware RAID support
- 1620W High-Efficiency Platinum Level Redundant Power Supplies (94% Efficiency)

<h3>Processor/Cache</h3>	<h3>Front Panel :</h3>						
<table border="1"> <tr> <td>Processor</td> <td>Dual AMD Opteron™ 6000 series (6300P* ready) processors (Socket G34) 16/12/8/4-Core ready; HT3.0 Link support</td> </tr> </table>	Processor	Dual AMD Opteron™ 6000 series (6300P* ready) processors (Socket G34) 16/12/8/4-Core ready; HT3.0 Link support	<table border="1"> <tr> <td>LEDs</td> <td>4x Power status LED, 4x UID LED, 4x Network activity LEDs, 4x System overheat / fan failed / power failed LED</td> </tr> <tr> <td>Buttons</td> <td>4x Power On/Off button, 4x UID button</td> </tr> </table>	LEDs	4x Power status LED, 4x UID LED, 4x Network activity LEDs, 4x System overheat / fan failed / power failed LED	Buttons	4x Power On/Off button, 4x UID button
Processor	Dual AMD Opteron™ 6000 series (6300P* ready) processors (Socket G34) 16/12/8/4-Core ready; HT3.0 Link support						
LEDs	4x Power status LED, 4x UID LED, 4x Network activity LEDs, 4x System overheat / fan failed / power failed LED						
Buttons	4x Power On/Off button, 4x UID button						
<h3>Chipset</h3>	<h3>Drive bays</h3>						
<table border="1"> <tr> <td>SR5670 + SP5100</td> </tr> </table>	SR5670 + SP5100	<table border="1"> <tr> <td>HDD bays</td> <td>24x Hot-swap 2.5" HDD (6 for each node)</td> </tr> <tr> <td>peripheral drives</td> <td>none</td> </tr> </table>	HDD bays	24x Hot-swap 2.5" HDD (6 for each node)	peripheral drives	none	
SR5670 + SP5100							
HDD bays	24x Hot-swap 2.5" HDD (6 for each node)						
peripheral drives	none						
<h3>System Memory</h3>	<h3>Power Supply</h3>						
<table border="1"> <tr> <td>Memory Capacity</td> <td>Eight DIMM sockets Up to 256GB DDR3 1866MHz ECC Registered DIMMs; 8x DIMM sockets</td> </tr> </table>	Memory Capacity	Eight DIMM sockets Up to 256GB DDR3 1866MHz ECC Registered DIMMs; 8x DIMM sockets	<table border="1"> <tr> <td>1620W High-Efficiency Platinum Level Redundant Power Supplies (94% Efficiency)</td> </tr> </table>	1620W High-Efficiency Platinum Level Redundant Power Supplies (94% Efficiency)			
Memory Capacity	Eight DIMM sockets Up to 256GB DDR3 1866MHz ECC Registered DIMMs; 8x DIMM sockets						
1620W High-Efficiency Platinum Level Redundant Power Supplies (94% Efficiency)							
<h3>Expansion Slots</h3>	<h3>Cooling System</h3>						
<table border="1"> <tr> <td>PCI-Express</td> <td>1x PCI-E 2.0 x16</td> </tr> </table>	PCI-Express	1x PCI-E 2.0 x16	<table border="1"> <tr> <td>4x 80mm PWM cooling fans</td> </tr> </table>	4x 80mm PWM cooling fans			
PCI-Express	1x PCI-E 2.0 x16						
4x 80mm PWM cooling fans							
<h3>Integrated On-Board</h3>	<h3>Form Factor</h3>						
<table border="1"> <tr> <td>SAS</td> <td>LSI 6Gbps SAS 2108 w/ Hardware RAID 0, 1, 10, 5, 50, and 6 support</td> </tr> <tr> <td>LAN</td> <td>2 RJ45 LAN ports 1 RJ45 Dedicated LAN supports IPMI</td> </tr> </table>	SAS	LSI 6Gbps SAS 2108 w/ Hardware RAID 0, 1, 10, 5, 50, and 6 support	LAN	2 RJ45 LAN ports 1 RJ45 Dedicated LAN supports IPMI	<table border="1"> <tr> <td>2U Twin2 Rackmount, Height 3.47" (88mm), Width 17.25" (438mm), Depth 28.5" (724mm)</td> </tr> </table>	2U Twin2 Rackmount, Height 3.47" (88mm), Width 17.25" (438mm), Depth 28.5" (724mm)	
SAS	LSI 6Gbps SAS 2108 w/ Hardware RAID 0, 1, 10, 5, 50, and 6 support						
LAN	2 RJ45 LAN ports 1 RJ45 Dedicated LAN supports IPMI						
2U Twin2 Rackmount, Height 3.47" (88mm), Width 17.25" (438mm), Depth 28.5" (724mm)							
<h3>Add-on Options</h3>	<p style="text-align: center;">Email : info@tyronesystems.com</p>						
<table border="1"> <tr> <td>RAID</td> <td>Optional</td> </tr> <tr> <td>optical drive</td> <td>None</td> </tr> </table>	RAID	Optional	optical drive	None	<p style="text-align: center;">For more/current product information, visit www.tyronesystems.com</p>		
RAID	Optional						
optical drive	None						