

Tyrone Camarero Specifications

Tyrone[®]

Camarero DA6003TR-28R

Key features

- Dual AMD Opteron™ 6000 series (6300 ready) processors
- Dual AMD SR5690 / SP5100 Chipset
- Up to 512GB DDR3 1600MHz ECC Registered DIMM; 16x DIMM sockets
- 3.2GHz HyperTransport (HT3) Link
- 3 PCI-E 2.0 x16 1 PCI-E 2.0 x8 2 PCI-E 2.0 x4 (in x8 slots)
- 6x SATA (3.0 Gb/s) ports + Intel 82576 dual-port Gigabit Ethernet LAN
- Integrated IPMI 2.0 + KVM with dedicated LAN
- Matrox G200eW Graphics
- 8x USB 2.0 ports (2x rear, 4x header, 2x Type A)
- 8x 4-pin PWM Fan & Speed control
- 12" x 13", 2U, 3U, 4U and above Server; E-ATX form factor
- 8x 3.5" Hot-swap SAS / SATA Drive Bays
- Gold Level Power Supply 720W Redundant High-efficiency



Processor/Cache	
Processor	Dual AMD Opteron™ 6000 series (6300 ready) processors
Chipset	
Dual AMD chipset SR5690/SP5100	
System Memory	
Up to 512GB DDR3 1600MHz ECC Registered DIMM; 16x DIMM sockets	
Expansion Slots	
3 PCI-E 2.0 x16 1 PCI-E 2.0 x8 2 PCI-E 2.0 x4 (in x8 slots)	
Integrated On-Board	
SATA	AMD SP5100 (RAID 0, 1, 10)
LAN	2 RJ45 LAN ports 1 RJ45 Dedicated LAN supports IPMI
Add-on Options	
RAID Card	Optional
Optical Drive	Optional

Drive bays
8x 3.5" Hot-swap SAS / SATA Drive Bays
Power Supply
720W Redundant High-efficiency 80 PLUS Gold Level Power Supply
Cooling System
3x 80x38mm 4-pin PWM Fans
Form Factor
2U 720W Redundant High-efficiency 80 PLUS Gold Level Power Supply
Width- 17.2" (437mm) , Height- 3.5" (89mm) , Depth – 25.5" (648mm)
Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com