

Tyrone Camarero Specifications

Tyrone[®]

Camarero DA600T3R-28R4

Key features

- Dual AMD Opteron™ 6000 Series processors (Socket G34) 16/12/8-Core ready
- Up to 768GB DDR3 Registered ECC 1600/1333/1066 SDRAM in 24 DIMMs
- 1 x UIO, 3 x PCI- E 2.0 x8
- 2x Intel 82576 (Dual-port Gb LAN) (4 ports)
- 8x Hot-swap SAS/S ATA Drive Bays
- 920W Redundant 80Plus Platinum Level (94%+)High-efficiency Power Supply
- Integrated IPMI 2.0 with Dedicated LAN



Processor/Cache	
Processor	Dual AMD Opteron™ 6000 Series processors (Socket G34) 16/12/8-Core ready
Chipset	
	AMD chipset SR5690 / SP5100
System Memory	
Memory Capacity	24 DIMM sockets up to 768GB DDR3 1600/1333/1066 MHz memory
Expansion Slots	
PCI-Express	3x PCI-E x8 (Gen 2.0); 1x UIO
Integrated On-Board	
SATA	AMD SP5100 (RAID 0, 1, 10)
LAN	4x RJ45 ports and 1x RJ45 Dedicated LAN supports IPMI
Add-on Options	
RAID	Optional
optical drive	Optional

Front Panel :	
LED Indicators	Power status,Hard drive activity, 2x Network activity ,Overheat status Powerfail
Switches	Power On/Off Button
Drive bays	
HDD bays	8x 3.5" SAS / SATA Hot-swap drive bays SAS or enterprise SATA HDD only recommended
peripheral bay	Slim DVD-ROM drive
Power Supply	
	920W Redundant 80Plus Platinum Level (94%+) High-efficiency Power Supply
Cooling System	
	4x 80x38mm 4-pin PWM Fans
Form Factor	
	2U Rackmount, Height -3.5" (89mm), Width- 17.2" (437mm), Depth – 27.75" (648mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	