

Tyrone Camarero Specifications



Camarero DI300TG-28

Key features

- Intel® Xeon® processor E5-2600 v3 product family
- Intel C-610 Chipset
- 24 memory sockets support up to 1.5TB total memory
- 8x 2.5" Hot-swap drive support
- 2 PCI Express* x24 riser Super Socket (supporting x8, x16, and PCI-X riser card slot options) 1 PCI Express Mixed x8 + x4 slot riser socket (supporting x4, and x8 riser card slot options)
- IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
- Dual 1-Gb Ethernet ports based on Intel® Ethernet Controller I350
- 1100W AC Redundant PSU (Platinum Efficiency)
- Intel® Xeon® Phi™ Support



Processor/Cache	
Processor	Intel® Xeon® processor E5-2600 v3 product family
Chipset	
	Intel C-610 Chipset
System Memory	
Memory Capacity	24 memory sockets support up to 1.5TB total memory
Expansion Slots	
PCI-Express	2 PCI Express* x24 riser Super Socket (supporting x8, x16, and PCI-X riser card slot options) 1 PCI Express Mixed x8 + x4 slot riser socket (supporting x4, and x8 riser card slot options)
Integrated On-Board	
SATA	10x SATA ports , Supports SW RAID 0, 1, 10, optional 5
LAN	Dual 1-Gb Ethernet ports based on Intel® Ethernet Controller I350
Add-on Options	
RAID Card	Optional

Front Panel	
Front	1xVGA and 2xUSB on dedicated tray
Buttons	Power On/Off button System Reset button
Drive Bays	
HDD Bays	8x 2.5" Hot-swap drive support
Power Supply	
	1100W AC Redundant PSU (Platinum Efficiency)
Cooling System	
	Redundant and hot-swap cooling fans
Form Factor	
	2U Rackmount
Dimension	17.25" wide x 28" long x 3.44"
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners