

Tyrone Camarero Specifications



Camarero DS1003TR-28R

Key features

- Dual Intel® Xeon® processor 5600/5500 series
- Intel® 5520 (Tylersburg) Chipset
- Up to 192GB DDR3 1333/ 1066/ 800MHz ECC Registered DIMM / 48GB Unbuffered DIMM
- Dual Intel® 82574L Gigabit Ethernet Controller
- 7x Low-profile, Full-length I/O Expansion Slot
- 4 (x8) PCI-E 2.0, 1 (x4) PCI-E 2.0 and 1 (x4) PCI-E slot
- Integrated Matrox G200eW Graphics
- Integrated IPMI 2.0 with Dedicated LANS
- 8x 3.5" Hot-swap SAS / SATA Drive Bays
- 7x Low-profile, Full-length I/O Expansion Slot
- 720W Redundant High-efficiency Gold Level Power Supply



Processor/Cache	
Processor	Dual Intel® Xeon® processor 5600/5500 Supports up to two Intel® 64-bit Xeon® processor(s)
Chipset	
	Intel® Xeon® processor 5520 Chip set
System Memory	
Memory Capacity	12x 240-pin DIMM sockets Supports up to 192 GB DDR3 ECC Reg DIMM
Expansion Slots	
PCI-Express	4 (x8) PCI-E 2.0 slots 1 (x4) PCI-E 2.0 slot 1 (x4) PCI-E slot
Integrated On-Board	
SATA	Intel ICH10R SATA 3.0Gbps Controller RAID 0, 1, 5, 10 support (Windows) RAID 0, 1, 10 support (Linux)
LAN IPMI LAN port	2x RJ45 LAN ports 1x RJ45 Dedicated
Add-on Options	
RAID Card	Optional
Optical Drive	None

Front Panel :	
LED Indicators	Power LED,Hard drive activity LED,2x Network activity LEDs,System Overheat LED,Power fail LED
Buttons	Power On/Off button, System Reset button
Drive bays	
HDD bays	8x 3.5" Hot-swap SAS / SATA drive bays
Peripheral Bays	Slim DVD-ROM drive (Optional)
Power Supply	
	720W Redundant High-efficiency 80 PLUS Gold Level Power Supply
Cooling System	
	3x 80x38mm 4-pin PWM Fans
Form Factor	
	2U Rack mount
Height	3.5" (89mm)
Width	17.2" (437mm)
Depth	25.5" (648mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	