

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS1003TU-14R

Key features

- Intel® Xeon® processor 5600/5500 series, with QPI up to 6.4 GT/s
- Up to 192GB DDR3 1333/ 1066/ 800MHz ECC Registered DIMM / 48GB Unbuffered DIMM
- Expansion slots : Left Side - 1 (x16) PCI-E 2.0 + 1 UIO or 1 (x16) PCI-E 2.0 , Right Side - 2 LAN optional
- Intel® 82576 Dual-Port Gigabit Ethernet Controller
- 6x SATA2 (3 Gbps) Ports via ICH10R Controller
- Integrated Matrox G200eW Graphics
- Integrated IPMI 2.0 with Dedicated LAN
- 4x 3.5" Hot-swap SAS / SATA Drive
- 700W High efficiency Redundant Power Supply



Processor/Cache	
Processor	Dual Intel® Xeon® processor 5600/5500series, with QPI up to 6.4 GT/s,Dual 1366-pin LGA Sockets
Chipset	
	Intel® 5520 (Tylersburg) chipset
System Memory	
	12x 240-pin DIMM sockets , Supports up to 192 GB 1333 / 1066 / 800MHz DDR3 ECC Registered memory
Expansion Slots	
Left Side	1 (x16) PCI-E 2.0 + 1 UIO slots or 1 (x16) PCI-E 2.0
Right Side	2 LAN optional
Integrated On-Board	
SATA	Intel ICH10R SATA 3.0Gbps Controller RAID 0, 1, 5, 10 support (Windows) RAID 0, 1, 10 support (Linux)
LAN	2x RJ45 LAN ports, 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	Optional

Front Panel	
Buttons	Power On/Off Button, System Reset Button,UID Button
LEDs	Power LED,Hard drive activity LED, 2x Network activity LEDs,Universal Information (UID) LED
Drive bays	
	4x 3.5" SATA Hot-swap drive trays
Power Supply	
	700W High efficiency Redundant Power Supply
Cooling System	
	4x 4cm Counter-rotating PWM fans
Form Factor	
	1U Rackmount Width- 17.2" (437mm) , Height- 1.7" (43mm) , Depth – 25.6" (650mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	