

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS20036R-28R4

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1.5TB ECC DDR3, up to 1866MHz; 24x DIMM sockets
- 4x PCI-E 3.0 x16 (low-profile) 1x PCI-E 3.0 x8 (low-profile) 1x PCI-E 3.0 x4 (in x8)
- Intel® i350 GbE Controller; 4x ports
- 8x Hot-swap 3.5" SAS/SATA HDD Bays
- 740W Redundant Power Supplies 80 Plus,Platinum Level



Processor/Cache		Front Panel :	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LED Indicators	Power LED,Hard drive activity LED,2x Network activity LEDs,System Overheat LED Power fail LED
		Switches	Power On/Off Button,System Reset Button
System Memory		Drive bays	
Memory Capacity	24x 240-pin DDR3 DIMM sockets Up to 1.5TB DDR3 ECC LRDIMM Up to 768GB DDR3 ECC Registered memory (RDIMM)	HDD bays	8x Hot-swap 3.5" SAS / SATA HDD trays
		Peripheral Bays	Slim DVD-ROM drive (optional)
Expansion Slots		Power Supply	
PCI-Express	4x PCI-E 3.0 x16 (low-profile, full-length) 1x PCI-E 3.0 x8 (low-profile, full-length) 1x PCI-E 3.0 x4 (in x8) (low-profile, full-length)		740W Redundant Power Supplies 80 Plus,Platinum Level
Integrated On-Board		Cooling System	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10		3x 8cm 7k RPM middle fans
SAS	SATA 3.0 6Gbps with RAID 0, 1, 5, 10		
LAN	SAS from C606 RAID 0, 1, 10 support 4x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port		
Add-on Options		Form Factor	
RAID Card	Optional		2U Rack mount
Optical Drive	Optional	Width	17.2" (437mm),
		Height	3.5" (89mm),
		Depth	25.5" (648mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	