

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS20036W-110R

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Add on card support: 2x PCI-E 3.0 x16 Full-height, Half-length slots
- Intel® i350 Dual port Gigabit Ethernet Controller; 2x LAN ports
- 10x Hot-swap 2.5" SAS/SATA HDD bays connected to onboard storage controller
- 700W Redundant Power Supplies 80 PLUS



Processor/Cache	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
Chipset	
Intel® C606 Chipset	
System Memory	
Memory Capacity	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)
Expansion Slots	
PCI-Express	2x PCI-E 3.0 x16 Full-height, Half-length slots
Integrated On-Board	
SATA	Upto 8 Hard disk SATA/SAS, SATA 3.0 6Gbps with RAID 0, 1, 5, 10 (On Board)
SAS	SAS from C606 RAID 0, 1, 10 support
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port (On Board)
Add-on Options	
RAID Card	Optional
Optical Drive	None

Front Panel :	
LED Indicators	Power LED Hard drive HDD activity 2x Network activity LEDs Universal Information (UID) LED
Switches	Power On/Off Button, System Reset Button, UID Button
Drive bays	
HDD bays	10x Hot-swap 2.5" SAS / SATA HDD trays (Add on card required for 10 HDD)
Peripheral Bays	None
Power Supply	
	700W Redundant Power Supplies, 80 Plus Gold Level Certified
Cooling System	
	5x 4cm Counter-rotating PWM Fans
Form Factor	
	1U Rackmount Width 17.2" (437mm), Height 1.7" (43mm), Depth 23.5" (597mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	