

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS20037R-316R4

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Intel® C602 Chipset
- Up to 1.5TB ECC DDR3, up to 1866MHz; 24x DIMM sockets
- 3x PCI-E 3.0 x16 slots (FHFL) and 1x PCI-E 3.0 x8 slot (FHHL)
- Intel® i350 GbE Controller; 4x ports
- 16x Hot-swap 3.5" SAS2 (with LSI expander) / SATA3 HDD Bays
- Hardware RAID controller and JBOD Expansion; RAID 0, 1, 5, 6, 10, 50, 60
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 3x Heavy duty PWM fans
- 920W Redundant Power Supplies Platinum Level (94%)



Processor/Cache		Front Panel	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LED Indicators	Power status LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Power fail LED
		Buttons	Power On/Off button System Reset button
Chipset		Drive Bays	
	Intel® C602 Chipset	Hot Swaps	16x Hot-swap 3.5" SAS / SATA Drive Bays.
		Optional OS Drive	2x Rear Hot-swap 2.5" Drive Bays
System Memory		Power Supply	
Memory Capacity	24x 240-pin DDR3 DIMM sockets. Up to 1.5TB DDR3 ECC LRDIMM Up to 768GB DDR3 ECC Registered memory (RDIMM)		920W high-efficiency (94%+) AC-DC Redundant power supplies with PMBus and I2C
Expansion Slots		Cooling System	
PCI-Express	3x PCI-E 3.0 x16 slots (Full-height, Full-length), 1x PCI-E 3.0 x8 slot (Full-height, Half-length)		3x 80mm Hot-swap 4-pin PWM Fans, 2x 80mm Rear-exhaust 4-pin PWM Fans
Integrated On-Board		Form Factor	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10. SATA 3.0 6Gbps with RAID 0, 1, 5, 10		3U Rackmount
SAS	LSI 2108 SAS2 RAID AOC (BBU optional), Hardware RAID 0, 1, 5, 6, 10, 50, 60		Width- 17.2" (437mm), Height- 5.2" (132mm) , Depth – 25.5" (648mm)
LAN	4x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port		
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	
Optical Drive	Optional		