

Tyrone Camarero Specifications



Camarero DS2003R-110R

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Add on card support: 2x PCI-E 3.0 x16 Full-height, Half-length slots
- Intel® i350 Dual port Gigabit Ethernet Controller; 2x LAN ports
- 10x Hot-swap 2.5" SAS/SATA HDD bays connected to onboard storage controller
- 700W Redundant Power Supplies 80 PLUS, Gold Level Certified



Processor/Cache		Front Panel	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LED	Power LED, Hard drive activity LED, 2x Network activity LEDs Universal Information (UID) LED
		Switches	Power On/Off Button
Chipset		Drive Bays	
	Intel® C606 Chipset	HDD Bays	10x Hot-swap 2.5" SAS / SATA HDD trays (connected to onboard storage controller)
		Peripheral Bays	None
System Memory		Power Supply	
Memory Capacity	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)		700W Redundant Power Supply 80 PLUS, Gold Level Certified
Expansion Slots		Cooling System	
PCI-Express	2x PCI-E 3.0 x16 Full-height, Half-length slots		5x 4cm Counter-rotating PWM Fans
Integrated On-Board		Form Factor	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10, SATA 3.0 6Gbps with RAID 0, 1, 5, 10		1U Rackmount Width * 17.2" (437mm), Height * 1.7" (43mm), Depth * 23.5" (597mm)
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port		
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	
Raid	Optional		
Optical Drive	None		