

Tyrone Camarero Specifications



Camarero DS2007T-224R

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2
- Intel® C602 Chipset
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 1x PCI-E 3.0 (x16) low-profile slot
- Intel® i350 Dual port Gigabit Ethernet
- 6x Hot-swap 2.5" SATA3/SAS2 HDD Bays per node
- 4x 8cm heavy duty PWM fans with optimal fan speed control
- 1620W Redundant Power Supplies Platinum Level (94%)



Processor/Cache	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2
Chipset	
Chipset	Intel® C602 Chipset
System Memory	
Memory Capacity	8x 240-pin DDR3 DIMM sockets, Up to 512GB DDR3 ECC LRDIMM
Expansion Slots	
PCI-Express	1x PCI-E 3.0 (x16) low-profile slot
Integrated On-Board	
SATA SAS	SATA 2.0 & 3.0 with RAID 0, 1, 5, 10 SAS2 (6Gbps) via LSI 2208 HW RAID supports 0, 1, 5, 6, 10, 50
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
Optical Drive	None

Front Panel	
LEDs	Power status LED, Hard drive activity LED, Information LED, 2x Network activity LEDs, Universal Information (UID) LED
Buttons	Power On/Off button UID button
Drive Bays	
HDD bays	6x Hot-swap 2.5" SATA3/SAS2 HDD trays
Power Supply	
	1620W Redundant Power Supplies Platinum Level (94%)
Cooling System	
	4x 8cm heavy duty PWM fans with optimal fan speed control
Form Factor	
Form Factor	2U Rackmount
	Width: 17.25" (438 mm), Height: 3.47" (88mm) , Depth: 26.75" (679mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	