

Tyrone Camarero Specifications



Camarero DS200T3G-14-2090

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 4x M2090 GPU cards pre-installed
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual-Port GbE Controller
- 4x Hot-swap 2.5" SATA Drive Bays
- 1800W Power Supply w/ PMBusV 80Plus Platinum Level (94%+)
- 12x Cooling Fans Total
- Smart server management tools



Processor/Cache		Front Panel :	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LEDs	Power LED,Hard drive activity LED, 2x Network activity LEDs, System Overheat LED / Fan fail LED /UID LED
Chipset	Intel® C602 Chipset	Switches	Power On/Off button,System Reset button
System Memory		Drive bays	
Memory Capacity	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)	HDD bays	4x 2.5" Hot-swap drive bays
Expansion Slots		Power Supply	
PCI-Express	4x M2090 GPU cards pre-installed	1800W Power Supply w/ PM Bus	
Integrated On-Board		Cooling System	
SATA	2 SATA 3.0 ports (6Gbps) 2 SATA 2.0 ports (3Gbps)	12x Counter-rotating Fans with optimal fan speed control	
LAN	2 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port	Form Factor	
Add-on Options		1U Rackmount	
RAID Card	Optional	Height	1.7" (43mm),
Optical Drive	None	Width	17.2" (437mm),
		Depth	31" (787mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	