

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

Camarero DS200T3G-14R-2075

## Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 3x PCI-E 3.0 x16 slots(support GPU/Xeon Phi cards)1x PCI-E 3.0 x8 (in x16) low-profile slot
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual-Port GbE Controller
- 4x Hot-swap 2.5" SATA Drive Bays
- 1800W Redundant Power Supplies 80Plus Platinum Level (94%+)
- 10x Counter rotating fans w/ optimal fan speed control
- Smart server management tools



| Processor/Cache     |  |
|---------------------|--|
| Processor           | Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family           |
| Chipset             |  |
| Intel® C602 Chipset |  |
| System Memory       |  |
| Memory Capacity     | 8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM, Up to 256GB DDR3 ECC Registered        |
| Expansion Slots     |  |
| PCI-Express         | 3x PCI-E 3.0 x16 slots (support GPU/Xeon Phi cards)<br>1x PCI-E 3.0 x8 (in x16) low-profile slot |
| Integrated On-Board |  |
| SATA                | SATA 2.0 & 3.0 with RAID 0, 1, 5, 10   |
| LAN                 | 2 RJ45 Gigabit Ethernet LAN ports,<br>1 RJ45 Dedicated IPMI LAN port                             |
| Add-on Options      |  |
| RAID Card           | Optional   |
| Optical Drive       | None   |

| Front Panel :  |  |
|--|--|
| LED Indicators   | 2x Network activity LEDs System Overheat LED / Fan fail LED / UID LED            |
| Switches   | Power On/Off Button  |
| Drive bays   |  |
| HDD bays   | 4x 2.5" Hot-swap drive bays  |
| Peripheral Bays  | Optional   |
| Power Supply   |  |
|  | 1800W Redundant Power Supplies 80 Plus Platinum Level (94%+)                     |
| Cooling System   |  |
|  | 10x counter-rotating fans with optimal fan speed control                         |
| Form Factor  |  |
|  | 1U Rackmount, Height - 1.7" (43mm), Width - 17.2" (437mm), Depth - 28.2" (716mm) |
| <p><b>Email: <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p> |  |