## **Tyrone Camarero Specifications**

## Camerero DS200T3G-210G-2090

## Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 4 (x16) PCI-E 3.0 slots (GPU card opt.),1 (x8) PCI-E 3.0 (in x16) slot, and low-profile slot
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual-Port GbE Controller
- 10x Hot-swap 2.5" SATA3 Drive Bays
- 1800W Redundant Power Supplies 80Plus Platinum Level (94%+)
- 5x heavy duty cooling fans
- Smart server management tools



Кеоп

| Processor/Cache                |  | Front Panel :                    |  |  |
|--------------------------------|--|----------------------------------|--|--|
|                                | Dual socket R (LGA 2011)<br>upports Intel® Xeon® processor   | LED Indicators                   | Power LED Hard drive activity LED 2x<br>Network activity LEDs System Overheat<br>LED / Fan fail LED /UID LED |  |
| E                              | 5-2600 and E5-2600 v2 family   | Switches                         | Power On/Off Button,System Reset<br>Button   |  |
| Chipset                        |  | Drive bays                       |  |  |
| Intel <sup>®</sup> C602 Chipse | t  | HDD bays                         | 10x 2.5" Hot-swap drive bays   |  |
| System Memory                  |  | Power Supply                     |  |  |
| Memory Capacity                | 8x 240-pin DDR3 DIMM sockets<br>Up to 512GB DDR3 ECC LRDIMM<br>Up to 256GB DDR3 ECC Registered<br>memory (RDIMM)                       |                                  | 1800W Redundant Power Supplies 80Plus<br>Platinum Level (94%+)   |  |
| Expansion Slots                |  | Cooling System                   |  |  |
| PCI-Express                    | 4 (x16) PCI-E 3.0 slots (4x NVIDIA<br>Tesla M2090 Fermi GPU cards.)<br>1 (x8) PCI-E 3.0 (in x16) slot<br>1 (x4) PCI-E 2.0 (in x8) slot | 5x 8cm heavy du                  | 5x 8cm heavy duty fans with optimal fan speed control  |  |
| Integrated On-Board            |  | Form Factor                      |  |  |
| SATA                           | SATA 2.0 3Gbps with RAID 0, 1, 5, 10<br>SATA 3.0 6Gbps with RAID 0, 1, 5, 10   | 2U Rackmount<br>Height :3.5" (89 |  |  |
| LAN                            | 2 RJ45 Gigabit Ethernet LAN ports 1<br>RJ45 Dedicated IPMI LAN port  | <b>v</b> ,                       | 437mm),  |  |
| Add-on Options                 | i  |                                  |  |  |
| RAID Card                      | Optional   | E : in                           | nfo@tyronesystems.com  |  |
| Optical Drive                  | None   |                                  | urrent product information, visit vw.tyronesystems.com   |  |

0 Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries

O specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners

