

Tyrone Camarero Specifications

Tyrone

Camarero DS200T3G-210R-2075

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 4 (x16) PCI-E 3.0 slots (GPU card opt.), 1 (x8) PCI-E 3.0 (in x16) slot, and low-profile slot
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual-Port GbE Controller
- 10x Hot-swap 2.5" SATA3 Drive Bays
- 1800W Redundant Power Supplies 80Plus Platinum Level (94%+)
- 5x heavy duty cooling fans
- Smart server management tools



Processor/Cache

Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
-----------	--

Chipset

Intel® C602 Chipset

System Memory

Memory Capacity	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)
-----------------	---

Expansion Slots

PCI-Express	4 (x16) PCI-E 3.0 slots (GPU card opt.) 1 (x8) PCI-E 3.0 (in x16) slot 1 (x4) PCI-E 2.0 (in x8) slot
-------------	--

Integrated On-Board

SATA	Intel ICH10R SATA 3.0Gbps Controller RAID 0, 1, 5, 10 support
LAN	2 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 Dedicated IPMI LAN port

Add-on Options

RAID Card	Optional
-----------	----------

Front Panel :

LED Indicators	Power LED Hard drive activity LED 2x Network activity LEDs System Overheat LED / Fan fail LED / UID LED
Switches	Power On/Off button System Reset button

Drive bays

HDD bays	10x 2.5" Hot-swap drive bays
----------	------------------------------

Power Supply

1800W Redundant Power Supplies 80Plus
Platinum Level (94%+)

Cooling System

5x 8cm heavy duty fans with optimal fan speed control

Form Factor

2U Rackmount	
Height	: 3.5" (89mm),
Width	: 17.2" (437mm),
Depth	: 31" (787mm)

E : info@tyronesystems.com

**For more/current product information, visit
www.tyronesystems.com**