

Tyrone Camarero Specifications



Camarero DS200T3R-14

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 1x PCI-E 3.0 x16 FHHL Expansion slot
- Intel® i350 Dual port Gigabit Ethernet
- 4x 3.5" Hot-swap SATA HDD Bays
- 600W High-efficiency Power Supply 80PLUS, Platinum Level (94%+)
- Power Saving Optimized & Improved Cooling, PUE-Optimized: 0°C ~ 47°C



Processor/Cache	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family†
Chipset	
Intel® C602 Chipset	
System Memory	
Memory Capacity	8x 240-pin DDR3 DIMM slots Supports up to 256 GB DDR3 ECC Registered memory (RDIMM) Supports up to 64 GB DDR3 ECC Un-Buffered memory (UDIMM)
Expansion Slots	
PCI-Express	1x PCI-E 3.0 x16 Full-height, Half-length
Integrated On-Board	
SATA	Cable for SATA controller SATA 2.0 (3Gbps) & 3.0 (6Gbps) with RAID 0, 1, 5, 10
LAN	2x RJ45 LAN ports 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	None

Front Panel :	
LED Indicators	Power status LED HDD activity LED 2x Network activity LEDs Universal Information (UID) LED
Switches	Power On/Off Button
Drive bays	
HDD bays	4x 3.5" Hot-swap 3.5" SATA HDD trays
Power Supply	
	600W High-efficiency Power Supply 80PLUS, Platinum Level (94%+)
Cooling System	
	5x 4cm Counter-rotating PWM fans
Form Factor	
	1U Rackmount Width 17.2" (437mm) Height 1.7" (43mm) Depth 25.6" (650mm)
<p>E : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	