

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS200T3R-26

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600
- Up to 256GB DDR3 1600MHz ECC Registered DIMM; 8x DIMM sockets
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM slots
- 1 PCI, 1 PCI-E 2.0 x1 3 PCI-E 3.0 x8, 1 PCI-E 2.0 x4 (in x8)
- Intel® 82574L GbE LAN, 2 ports
- 8x SATA2 and 2x SATA3 ports
- 6x 3.5" Hot-swap SAS / SATA Drive Bays
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 9x USB 2.0 ports (4 rear, 4 via header + 1 Type A)
- 4x 80mm 6300 RPM Fans
- 650W High-efficiency Power Supply Gold Level Certified



Processor/Cache	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600
Chipset	
Intel® C602 Chipset	
System Memory	
Memory Capacity	8x 240-pin DDR3 DIMM sockets Supports up to 256 GB DDR3 ECC
Expansion Slots	
PCI-Express	3 PCI-E 3.0 x8, 1 PCI-E, 2.0 x4 (in x8) , 1 PCI-E 2.0 x , 1 PCI (Low Profile)
Integrated On-Board	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 , SATA 3.0 6Gbps with RAID 0, 1, 5, 10
LAN	2 RJ45 Gigabit Ethernet LAN ports , 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID	Optional
Optical Drive	Optional

Front Panel	
Buttons	Power On/Off button , System Reset button
LED Indicators	Power LED, Hard drive activity LED, 2x Network activity LEDs , System Overheat LED
Drive bays	
HDD bays	6x 3.5" SATA HDD bays,
Power Supply	
	650W High-efficiency Power Supply 80 PLUS, Gold Level Certified
Cooling System	
	4x 80mm 6300 RPM fans
Form Factor	
	2U Rackmount Width- 16.8" (426mm), Height- 3.5" (89mm) , Depth – 25.6" (650mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	