

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS200T3R-34

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Expansion slots: 3 (x16) PCI-E 3.0, 2 (x8) PCI-E 3.0 & 1 (x4) PCI-E 3.0
- Intel® i350 Dual port Gigabit Ethernet
- 2x SATA3 and 8x SATA2 ports
- 4x 3.5" SATA HDD Bays (90° rotatable drive cage) Enterprise SATA HDD only recommended
- 900W High Efficiency Power Supply 80PLUS, Gold Level Certified



Processor/Cache	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
Chipset	
Intel® C602 Chipset	
System Memory	
Memory Capacity	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512G
Expansion Slots	
PCI-Express	3 (x16) PCI-E 3.0 slots 2 (x8) PCI-E 3.0 slots 1 (x4) PCI-E 3.0 slots
Integrated On-Board	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1
LAN	2x RJ45 Gigabit Ethernet LAN ports
Add on Options	
RAID	Optional
Optical Drive	Optional

Front Panel :	
LED Indicators	Power LED Hard drive activity LED Network activity LED System Overheat LED
Switches	Power On/Off button
Drive bays	
HDD bays	4x 3.5" SATA HDD Bays (90° rotatable drive cage) Enterprise SATA HDD only recommended
Peripheral Bays	2x 5.25" peripheral drive bays 1x 3.5" peripheral drive bay
Power Supply	
900W High Efficiency Power Supply 80PLUS, Gold Level Certified	
Cooling System	
1x 12cm (1850rpm) rear exhaust fan 1x 12cm (1850rpm) front cooling fan Optimized cooling technology for Whisper-Quiet Operation	
Form Factor	
Mid-Tower	
Height	16.7" (424mm)
Width	7.6" (193mm)
Depth	20.68" (525.3mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	