

Tyrone Camarero Specifications

Tyrone

Camarero DS200T3T-26R

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- 1x MicroLP PCI-E 3.0 x8 slot
- Intel® i350 Dual port Gigabit Ethernet
- 6x Hot-swap 3.5" SATA HDD Bays
- 1280W Redundant Power Supplies 80 PLUS, Platinum Level



Processor/Cache	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
Chipset	
Intel® C602 Chipset	
System Memory	
Memory Capacity	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)
Expansion Slots	
PCI-Express	1 Micro Low Profile PCI-E 3.0 x8 slot MicroLP Adapter Matrix
Integrated On-Board	
SATA	SATA 2.0 & 3.0 with RAID 0, 1, 5, 10
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional

Front Panel :	
LED Indicators	Power LED Hard drive activity LED 2x Network activity LEDs System Overheat LED / Fan fail LED / UID LED
Switches	Power On/Off button System Reset button
Drive bays	
HDD bays	6x Hot-swap 3.5" SATA HDD trays
Power Supply	
1280W Redundant Power Supplies 80 PLUS, Platinum Level	
Cooling System	
4x 8cm heavy duty PWM fans with optimal fan speed control	
Form Factor	
2U Rackmount	
Width	:17.25" (438mm),
Height	:3.47" (88mm),
Depth	:28.5" (724mm)
<p>E : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	