

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

## Camarero DS200T6G-48R

### Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- 4 PCI-3.0x16 (support 4x double width GPU cards), 2PCI-E-3.0x8(1x16),1PCI-E-2.0x4(8)
- Intel® i350 Dual port Gigabit Ethernet
- 2x SATA3 and 8x SATA2 ports
- 8x Hot-swap 3.5" HDD Bays
- 1620W Redundant Power Supplies 80 PLUS, Platinum Level (94%)
- Tower or Rackmount



Processor/Cache		Front Panel	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LED	Power LED,Hard drive activity LED, 2x Network activity LEDs System Overheat LED
		Switches	Power On/Off Button
Chipset		Drive Bays	
	Intel® C602 Chipset	HDD Bays	8x Hot-swap 3.5" SAS/SATA Drive Trays
		Peripheral Bays	3x 5.25" drive bays in storage module - rotates 90° for Rackmount 1x 3.5" fixed drive bay
System Memory		Power Supply	
Memory Capacity	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)		1620W Redundant Power Supplies, 80 PLUS, Platinum Level (94%)
Expansion Slots		Cooling System	
PCI-Express	4 PCI-3.0x16 (support 4x double width GPU cards), 2PCI-E-3.0x8(1x16), 1PCI-E-2.0x4(8)		4x 92x38mm 4-pin PWM Middle Cooling Fans 2x 80x38mm 4-pin PWM Rear Exhaust Fans
Integrated On-Board		Form Factor	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10, SATA 3.0 6Gbps with RAID 0, 1		4U Rackmount/Tower, Height 18.2" (462mm), Width 7.0" (178mm), Depth 26.5" (673mm)
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port		
Add-on Options		<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	
Raid	Optional		
Optical Drive	Optional		