Tyrone Camarero Specifications

Camarero DS200T6R-28R

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 .
- and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets 3x PCI-E 3.0 x16, 3x PCI-E 3.0 x8
- Intel[®] i350 Dual port Gigabit Ethernet
- 2x SATA3 and 8x SATA2 ports
- 8x Hot-swap 3.5" SATA HDD Bays
- 740W Redundant Power Supplies 80 Plus, Platinum Level





Processor/Cache

Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family

Chipset

Intel® C602 Chipset

System Memory:

16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)

Expansion Slots:

3x PCI-E 3.0 x16 3x PCI-E 3.0 x8

Integrated On-Board

SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1, 5, 10

LAN:2x RJ45 Gigabit Ethernet LAN ports

1x RJ45 Dedicated IPMI LAN port

Add-on Options

RAID card optional

Optical Drive Optional

Front Panel:

LED Indicators: Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED Power fail LED

Switches: Power On/Off Button, System Reset Button

Drive bays

HDD bays 8x Hot-swap 3.5" SATA HDD trays

Peripheral Bays:Slim DVD-ROM drive (optional)

Power Supply

740W Redundant Power Supplies 80 Plus, Platinum Level

Cooling System

3x 8cm 7k RPM middle fans

Form Factor

2U Rack mount

Width 17.2" (437mm) Height 3.5" (89mm) Depth 25.5" (648mm)

> Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com

O Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries
O Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners