


Tyrone Camarero Specifications

Tyrone[®]

Camarero DS200T6R-424R

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- intel® C602J chipset
- 24 x 3.5" Hot-swap drive bays
- Up to 1TB ECC DDR3, up to 1866MHz;16x DIMM sockets
- 6 (x8) PCI-E 3.0
- Intel® i350 Dual port GbE LAN
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 4x SATA2 and 2x SATA3 ports
- 920W Redundant Power Supplies



Processor/Cache		Front Panel :	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LEDs	Power LED,Hard drive activity LED,2x Network activity LEDs,System Overheat LED,Power Fail LED
		Buttons	Power On/Off button,System Reset button
Chipset		Drive bays	
	Intel® C602J chipset	HDD bays :	24 x 3.5" hot swap SAS Drive bays
		Peripheral Bays:	None
System Memory		Power Supply	
Memory Capacity	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC RDIMM	920W Redundant Power Supplies 80 PLUS, Platinum Level (94%)	
Expansion Slots		Cooling System	
PCI-Express	6 (x8) PCI-E 3.0	3x 80mm Hot-swap 4-pin PWM Fans 2x 80mm Rear-exhaust 4-pin PWM Fans	
Integrated On-Board		Form Factor	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA3.0 6Gbps with RAID 0, 1, 5, 10	4U Storage Chassis with Expender for Scalability	
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x I LAN port	Height 7" (178mm) Width 17.2" (437mm) Depth 26" (660mm)	
Add-on Options		Email : info@tyronesystems.com	
RAID card optional		For more/current product information, visit	
Optical Drive : None		www.tyronesystems.com	