

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS200T6R-48

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Expansion slots: 3 (x16) PCI-E 3.0, 2 (x8) PCI-E 3.0 & 1 (x4) PCI-E 3.0
- Intel® i350 Dual port Gigabit Ethernet
- 2x SATA3 and 8x SATA2 ports
- 8x Hot-swap 3.5" SATA HDD Bays
- 1200W High Efficiency Power Supply 80 PLUS, Platinum Level (94%)
- RealTek ALC889 7.1 High Definition Audio with S/PDIF header
- Tower or Rackmount



Processor/Cache	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
Chipset	
	Intel® C602 Chipset
System Memory	
Memory Capacity	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)
Expansion Slots	
PCI-Express	3 (x16) PCI-E 3.0 slots 2 (x8) PCI-E 3.0 slots 1 (x4) PCI-E 3.0 slot
Integrated On-Board	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1, 5, 10
LAN	2x RJ45 Gigabit Ethernet LAN ports
Add-on Options	
Raid	Optional
ODD	Slim DVD-ROM drive (optional)
Audio	RealTek ALC889 7.1 High Definition Audio with S/PDIF header

Front Panel	
LED	2x Network activity LEDs System Overheat / Fan Fail LED
Switches	Power On/Off Button
Drive Bays	
HDD Bays	8x Hot-swap 3.5" SATA Drive Trays
Peripheral Bays	2x 5.25" Peripheral Drive Bay 1x 5.25" Bay for Floppy Drive
Power Supply	
	1200W High Efficiency Power Supply 80 PLUS, Platinum Level (94%)
Cooling System	
	2x 80mm PWM Super Quiet Fans 1x 92mm PWM Super Quiet Rear Fan
Form Factor	
	4U Rackmountable / Tower, Height 17.8" (452mm), Width 7.0" (178mm), Depth 25.5" (648mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	