

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

## Camarero DS200T6R-48R

### Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Expansion slots: 10x PCI-E 3.0 x8, 1x PCI-E 2.0 x4 (in x8)
- Intel® i350 Dual port Gigabit Ethernet
- 8x 3.5" Hot-swap HDD Bays
- 3x 5.25" Peripheral Drive Bays
- 1280W Redundant Power Supplies 80 PLUS, Platinum Level (94%)
- Tower or Rackmount



<b>Processor/Cache</b>		<b>Front Panel :</b>	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LED Indicators	2x Network activity LEDs System Overheat LED Power Fail LED
		Switches	Power On/Off Button
<b>Chipset</b>		<b>Drive bays</b>	
Intel® C602 Chipset		HDD bays	8x Hot-swap 3.5" Drive Trays
		Peripheral Bays	3x 5.25" Peripheral Drive Trays
<b>System Memory</b>		<b>Power Supply</b>	
Memory Capacity	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)	1280W Redundant Power Supplies 80 PLUS, Platinum Level (94%)	
<b>Expansion Slots</b>		<b>Cooling System</b>	
PCI-Express	10x PCI-E 3.0 x8 1x PCI-E 2.0 x4 (in x8)	4x 92x38mm 4-pin PWM middle fans 2x 80x38mm 4-pin PWM rear exhaust fans	
<b>Integrated On-Board</b>		<b>Form Factor</b>	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 , SATA 3.0 6Gbps with RAID 0, 1, 5, 10	4U Rackmount/Tower, Height 17.2" (437mm), Width 7.0" (178mm), Depth 26.5" (673mm) "	
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port		
<b>Add-on Options</b>		<b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b>	
RAID	Optional	<b>For more/current product information, visit</b>	
Optical Drive	Optional	<b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b>	