

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS200TR-12

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Intel® C602 Chipset
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 1x PCI-E 3.0 x16 FHHL Expansion slot
- Intel® i350 Dual port Gigabit Ethernet
- 2x 3.5" Hot-swap SATA HDD Bays
- 2x 10cm PWM blower fans
- 350W High-efficiency Power Supply Gold Level Certified



Processor/Cache		Front Panel	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LED Indicators	Power status LED, HDD activity LED, 2x Network activity LEDs, Universal Information (UID) LED
		Buttons	Power On/Off button System Reset button
Chipset		Drive Bays	
Chipset	Intel® C602 Chipset	HDD bays	2x 3.5" Hot-swap SATA HDD trays
System Memory		Power Supply	
Memory Capacity	8x 240-pin DDR3 DIMM Sockets, supports up to 256 GB DDR3 ECC Registered memory (RDIMM)		350W High-efficiency Power Supply Gold Level Certified
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x16 FHHL Expansion slot		2x 10cm PWM blower fans
Integrated On-Board		Form Factor	
SATA	Via Cable for SATA controller SATA 3.0 (6Gbps) with RAID 0, 1	Form Factor	1U Rackmount
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port		Width: 17.2" (437 mm), Height: 1.7" (43mm) , Depth: 25.6" (650mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid	Optional		
Optical Drive	None		