


Tyrone Camarero Specifications



Camarero DS2B0T3U-14

Key features

- Dual socket B2 (LGA 1356) supports Intel® Xeon® processor E5-2400 v2
- Up to 384GB DDR3 1600MHz ECC R/LRDIMM; 12x DIMM sockets
- Riser card support: 2x PCI-E 3.0 x8 (1 FHFL, 1 FHHL) slots
- Intel® i350 Dual port Gigabit Ethernet Controller; 2x LAN ports
- 4x Hot-swap 3.5" SATA HDD Bays
- 600W High-efficiency Power Supply 80 PLUS, Gold Level Certified



Processor/Cache	
Processor	Intel® Xeon® processor E5-2400 v2
Chipset	
Intel® C602 Chipset	
System Memory	
Memory Capacity	12x 240-pin DDR3 DIMM sockets Supports up to 384 GB DDR3 ECC
Expansion Slots	
PCI-Express	2x PCI-E 3.0 x8 (1 Full-height Full-length, 1 Full-height Half-length)
Integrated On-Board	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1
LAN	2 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	Optional

Front Panel :	
LEDs	Power status LED,HDD activity LED, 2x Network activity LEDs,Universal Information (UID) LED
Switches	Power On/Off button,System Reset button, UID button
Drive bays	
HDD bays	4x Hot-swap 3.5" SATA HDD trays
Peripheral Bays	Slim DVD-ROM drive (Optional)
Power Supply	
600W High-efficiency Power Supply Gold Level Certified power supply	
Cooling System	
2x Blower fans with Optimal Fan Speed Control	
Form Factor	
1U Rackmount	
Width	17.2" (437mm),
Height	1.7" (43mm),
Depth	25.6" (650mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	