

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

## Camarero DS30012E1-460RL

### Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family
- Intel® C612 chipset
- Up to 3TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 24x DIMM slots
- 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8
- SIOM for flexible networking options
- 60x 3.5" Hot-swap SAS3/SATA3 drive bays; 2x 2.5" rear Hot-swap SATA3 drive bays; optional 6x NVMe bays
- LSI 3008 SAS3 IT mode controller
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 5x 8cm hot-swap redundant PWM fans PWM fans
- 2000W Redundant Power Supplies Titanium Level (96%) Certified
- Front 3.5" LCD display



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family	LED Indicators	Power LED,Hard drive activity LED, 2x Network activity LEDs,System Overheat LED,Power Fail LED
		Buttons	Power On/Off button, System Reset button
Chipset		Drive Bays	
Chipset	Intel® C612 chipset	HDD Bay	60x 3.5" Hot-swap SAS3/SATA3 drive bays,2x 2.5" rear Hot-swap SATA3 drive bays,6x NVMe bays (optional)
System Memory		Power Supply	
Memory Capacity	24x 288-pin DDR4 DIMM slots , Up to 3TB ECC 3DS LRDIMM, 768 ECC RDIMM	2000W Redundant Power Supplies Titanium Level (96%) Certified	
Expansion Slots		Cooling System	
PCI-Express	2x PCI-E 3.0 x16 slots, 1x PCI-E 3.0 x8 slots	2x 80mm hot-swap rear exhaust cooling fans, Redundant cooling	
Integrated On-Board		Form Factor	
SAS	LSI 3008 SAS3 IT mode	4U Rackmount	
		Width:	17.2" (437mm) ,
		Height:	7" (178mm),
		Depth:	30.2" (767mm)With Cable Management Arm Installed: 35.2" (895mm)
Add-on Options		<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	
Optical Drive	None		