

Tyrone Camarero Specifications

Camarero DS3003T-14R

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family; QPI up to 9.6GT/s
- Intel® C612 chipset
- Up to 2TB† ECC 3DS LRDIMM , up to DDR4- 2400†MHz ; 16x DIMM slots
- 1x PCI-E 3.0 x16 Low-profile slot and 1x "O slot"
- Intel® i350 Dual port GbE LAN
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- 4x 2.5" Hot-swap SAS3 drive bays
- Broadcom 3008 SAS3 controller; SW RAID
- 1000W Redundant Power Supplies Titanium Level (96%)



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family; QPI up to 9.6GT/s	Led's	Power status LED,Network activity LED, Universal Information (UID) LED
		Buttons	Power On/Off button,UID button/LED
Chipset		Drive Bays	
Chipset	Intel® C612 chipset	HDD bays	4x 2.5" Hot-swap SAS3 drive bays
System Memory		Power Supply	
Memory Capacity	16x 288-pin DDR4 DIMM slots,Up to 2TB† ECC 3DS LRDIMM, 512GB ECC RDIMM	1000W Redundant Power Supplies Titanium Level (96%)	
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x16 Low-profile slot and 1x "O slot"	3x heavy duty counter rotating fans with air shroud and optimal fan speed control	
Integrated On-Board		Form Factor	
SAS	Broadcom 3008 SAS3 (12Gbps) controller; SW RAID 0, 1, 10 support	Form Factor	1U Rackmount
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Height	: 1.7" (43mm)
		Width	: 17.2" (437mm)
		Depth	: 28.25" (718mm)
Add-on Options		Email : info@tyronesystems.com	
Optical Drive	None	For more/current product information, visit www.tyronesystems.com	