Tyrone Camarero Specifications

Tvrone

Camarero DS3007E1-436RT

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/v3 family
- Intel® C612 chipset
- Up to 3TB ECC 3DS LRDIMM, up to DDR4- 2400MHz; 24x DIMM slots
- 2 PCI-E 3.0 x16, 3 PCI-E 3.0 x8.1 PCI-E 2.0 x4 (in x8) Slot 3 &4 occupied by controller and JBOD expansion port
- Qual 10GBase-T LAN w/ Intel® X540
- 36x 3.5" Hot-swap SAS3/SATA3 drive bays (24 front + 12 rear); 4x 2.5" internal fixed drive bays
- SAS3 via LSI 3108 AOC (HW RAID)
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 7x 80mm middle cooling fans
- 1280W Redundant Power Supplies Platinum Level (94%)





Processor/Cache

Dual socket R3 (LGA 2011) supports Processor

Intel® Xeon® processor E5-2600

v4/v3 family

Chipset

Intel® C612 chipset Chipset

System Memory

Memory Capacity 24x 288-pin DDR4 DIMM slots,Up to

3TB ECC 3DS LRDIMM, 1.5TB ECC RDIMM

Expansion Slots

PCI-Express 2x PCI-E 3.0 x16 slot,3x PCI-E 3.0 x8 slot,

1x PCI-E 2.0 x4 (in x8) slots, Slot 3 & 4

occupied by controller and **JBOD Expansion Port**

Integrated On-Board

SAS SAS3 (12Gbps) via LSI 3108 AOC;

HW RAID 0,1,5,6,10,50,60

SATA SATA3 (6Gbps) with RAID 0, 1, 5, 10 LAN 4x RJ45 10GBase-T LAN ports,1x RJ45

Dedicated IPMI LAN port

Add-on Options

Optical Drive None

Front Panel

LED Indicators Power status LED, Hard drive activity LED,

> 2x Network activity LEDs, System Overheat LED, Power fail LED

Buttons Power On/Off Button, System Reset Button

Drive Bays

HDD bays 36x 3.5" Hot-swap SAS3/SATA3 drive bays,

Double-sided: 24 front + 12 rear drive bays

Power Supply

1280W Redundant Power Supplies Platinum Level (94%)

Cooling System

7x 80mm middle cooling fans, Redundant cooling

Form Factor

Form Factor **4U Rackmount**

Height : 7" (178mm), Width 17.2" (437mm), 27.5" (699mm) Depth

Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com